


**HSX321SL SERIES****SEAM SEALING PACKAGE**

☒ RoHS Compliant
 ☒ Pb Free

**STANDARD SPECIFICATION**

Items	Parameter		
Frequency Range	12~16MHz	16~32MHz	32~54MHz
Mode	Fundamental		
Frequency Tolerance (at.25℃)	± 10ppm		
Load Capacitance	7pF Min.		
Drive Level	10μW (300μW Max.)		
Equivalent Series Resistance	80Ω Max.	50Ω Max.	40Ω Max.
Storage Temp. Range	-55 ~ +125℃		

FREQUENCY STABILITY OVER OPERATING TEMPERATURE RANGE




Operating Temperature	Stability
-30 ~ +85℃	± 10 ppm
-40 ~ +105℃	± 20 ppm
-40 ~ +125℃	± 30 ppm

*For other specification, please contact us.



Packing Unit : 3,000pcs/Reel.

DIMENSION

Unit:mm

**Bottom View**

Pin Connections	
#1	Crystal
#2	GND/Lid
#3	Crystal
#4	GND/Lid

Internal Connection (Top View)**Recommended Land Pattern
Tolerance: ±0.1**

Actual Size ☐

单击下面可查看定价，库存，交付和生命周期等信息

[>>HELE\(加高\)](#)