

HSX321SK SERIES

SEAM SEALING PACKAGE

☒ RoHS Compliant
 ☒ Pb Free
 ☒ AEC Qualified



STANDARD SPECIFICATION

Items	Parameter			
Frequency Range	8MHz	10~20MHz	20~32MHz	32~54MHz
Mode	Fundamental			
Frequency Tolerance (at.25°C)	±7ppm ~ ±10ppm			
Load Capacitance	6pF Min.			
Drive Level	10μW (300μW Max.)			
Equivalent Series Resistance	150Ω Max.	80Ω Max.	50Ω Max.	40Ω Max.
Storage Temp. Range	-55 ~ +125°C			

FREQUENCY STABILITY OVER OPERATING TEMPERATURE RANGE



Operating Temperature	Stability
-40 ~ +85°C	±15 ppm
-40 ~ +105°C	±20 ppm
-40 ~ +125°C	±30 ppm

*For other specification, please contact us.

Packing Unit : 3,000pcs/Reel.


DIMENSION

Unit:mm




Pin Connections	
#1	Crysta
#2	GND/Lid
#3	Crysta
#4	GND/Lid

Internal Connection (Top View)



Recommended Land Pattern Tolerance: ±0.1



Actual Size ☐

单击下面可查看定价，库存，交付和生命周期等信息

[>>HELE\(加高\)](#)