

## DAISY-7X1-W2

~50° wide beam with tighter cutoff

### SPECIFICATION:

Dimensions	279.5 x 39.6 mm
Height	20.3 mm
Fastening	pin, screw, clips
ROHS compliant	yes ⓘ

### MATERIALS:



Component	Type	Material	Colour	Finish	Length (mm)
C16989_DAISY-7X1-W2	Linear lens	PMMA	clear		
C19855_DAISY-7X1-SHD3-MATT-GLD	Shade	PC	gold	matt	
C19854_DAISY-7X1-SHD3-MATT-RED	Shade	PC	red	matt	
C19853_DAISY-7X1-SHD3-MATT-GR	Shade	PC	grey	matt	
C19852_DAISY-7X1-SHD-MATT-GLD	Shade	PC	gold	matt	
C19764_DAISY-7X1-SHD-MATT-GR	Shade	PC	grey	matt	
C19763_DAISY-7X1-SHD-MATT-RED	Shade	PC	red	matt	
C19642_DAISY-7X1-SHD3-MET-MATT	Shade	PC	metal	matt	
C19641_DAISY-7X1-SHD3-MET	Shade	PC	metal	gloss	
C19315_DAISY-7X1-SHD3-WHT-MATT	Shade	PC	white	matt	
C19314_DAISY-7X1-SHD3-WHT	Shade	PC	white	gloss	
C19313_DAISY-7X1-SHD3-MATT	Shade	PC	black	matt	
C19312_DAISY-7X1-SHD3	Shade	PC	black	gloss	
C18409_DAISY-7X1-SHD-MET-MATT	Shade	PC	metal	matt	
C18167_DAISY-7X1-SHD-MET	Shade	PC	metal	gloss	
C17225_DAISY-7X1-SHD-WHT-MATT	Shade	PC	white	matt	
C17051_DAISY-7X1-SHD-MATT	Shade	PC	black	matt	
C16876_DAISY-7X1-SHD-WHT	Shade	PC	white	gloss	
C16872_DAISY-7X1-SHD	Shade	PC	black	gloss	



**ORDERING INFORMATION:**

**Quantities for one set:**

Linear lens 1

Shade 1

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C16989_DAISY-7X1-W2	Linear lens	312	312	24	7.0
» Box size: 400 x 300 x 300 mm					
C17051_DAISY-7X1-SHD-MATT	Shade	156	312	24	7.3
» Box size: 595 x 360 x 230 mm					
C19854_DAISY-7X1-SHD3-MATT-RED	Shade	156	312	24	6.2
» Box size: 595 x 360 x 230 mm					
C19313_DAISY-7X1-SHD3-MATT	Shade	156	312	24	5.8
» Box size: 595 x 360 x 230 mm					
C19763_DAISY-7X1-SHD-MATT-RED	Shade	156	312	24	7.1
» Box size: 595 x 360 x 230 mm					
C17225_DAISY-7X1-SHD-WHT-MATT	Shade	156	312	24	7.6
» Box size: 595 x 360 x 230 mm					
C19855_DAISY-7X1-SHD3-MATT-GLD	Shade	156	312	24	6.2
» Box size: 595 x 360 x 230 mm					
C19314_DAISY-7X1-SHD3-WHT	Shade	156	312	24	6.3
» Box size: 595 x 360 x 230 mm					
C16872_DAISY-7X1-SHD	Shade	156	312	24	7.1
» Box size: 595 x 360 x 230 mm					
C19764_DAISY-7X1-SHD-MATT-GR	Shade	156	312	24	5.7
» Box size: 595 x 360 x 230 mm					
C18167_DAISY-7X1-SHD-MET	Shade	156	312	24	7.0
» Box size: 595 x 360 x 230 mm					
C19315_DAISY-7X1-SHD3-WHT-MATT	Shade	156	312	24	6.2
» Box size: 595 x 360 x 230 mm					
C16876_DAISY-7X1-SHD-WHT	Shade	156	312	24	7.6
» Box size: 595 x 360 x 230 mm					
C19852_DAISY-7X1-SHD-MATT-GLD	Shade	156	312	24	7.1
» Box size: 595 x 360 x 230 mm					
C18409_DAISY-7X1-SHD-MET-MATT	Shade	156	312	24	7.0
» Box size: 595 x 360 x 230 mm					
C19641_DAISY-7X1-SHD3-MET	Shade	156	312	24	6.1
» Box size: 595 x 360 x 230 mm					
C19853_DAISY-7X1-SHD3-MATT-GR	Shade	156	312	24	7.1
» Box size: 595 x 360 x 230 mm					
C19312_DAISY-7X1-SHD3	Shade	156	312	24	6.1
» Box size: 595 x 360 x 230 mm					
C19642_DAISY-7X1-SHD3-MET-MATT	Shade	156	312	24	5.7
» Box size: 595 x 360 x 230 mm					





See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

### OPTICAL RESULTS (MEASURED):





**LED** LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm  
**FWHM / FWTM** 58.0° / 68.0°  
**Efficiency** 85 %  
**Peak intensity** 1.2 cd/lm  
**LEDs/each optic** 4  
**Light colour/type** White  
**Required components:**  
 C17051\_DAISY-7X1-SHD-MATT



Light distribution files




**LED** LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm  
**FWHM / FWTM** 58.0° / 69.0°  
**Efficiency** 92 %  
**Peak intensity** 1.2 cd/lm  
**LEDs/each optic** 4  
**Light colour/type** White  
**Required components:**  
 C18167\_DAISY-7X1-SHD-MET



Light distribution files



**LED** LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm  
**FWHM / FWTM** 58.0° / 68.0°  
**Efficiency** 92 %  
**Peak intensity** 1.2 cd/lm  
**LEDs/each optic** 4  
**Light colour/type** White  
**Required components:**  
 C16876\_DAISY-7X1-SHD-WHT




Light distribution files

### OPTICAL RESULTS (MEASURED):





LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm  
FWHM / FWTM 58.0° / 68.0°  
Efficiency 92 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17225\_DAISY-7X1-SHD-WHT-MATT



Light distribution files





LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm  
FWHM / FWTM 58.0° / 68.0°  
Efficiency 85 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C16872\_DAISY-7X1-SHD



Light distribution files



LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm  
FWHM / FWTM 58.0° / 68.0°  
Efficiency 91 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17533\_DAISY-7X1-SHD-MET-MATT





Light distribution files

### OPTICAL RESULTS (MEASURED):



LED LUXEON 2835 Line  
FWHM / FWMTM 58.0° / 69.0°  
Efficiency 92 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17532\_DAISSY-7X1-SHD-MET



Light distribution files





LED LUXEON 2835 Line  
FWHM / FWMTM 58.0° / 69.0°  
Efficiency 91 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17533\_DAISSY-7X1-SHD-MET-MATT

Light distribution files



LED LUXEON 2835 Line  
FWHM / FWMTM 58.0° / 69.0°  
Efficiency 92 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C16876\_DAISSY-7X1-SHD-WHT





Light distribution files

### OPTICAL RESULTS (MEASURED):





LED LUXEON 2835 Line  
 FWHM / FWTM 58.0° / 69.0°  
 Efficiency 92 %  
 Peak intensity 1.2 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C17225\_DAISSY-7X1-SHD-WHT-MATT



Light distribution files





LED LUXEON 2835 Line  
 FWHM / FWTM 58.0° / 68.0°  
 Efficiency 85 %  
 Peak intensity 1.2 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C16872\_DAISSY-7X1-SHD



Light distribution files



LED LUXEON 2835 Line  
 FWHM / FWTM 58.0° / 68.0°  
 Efficiency 85 %  
 Peak intensity 1.2 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C17051\_DAISSY-7X1-SHD-MATT





Light distribution files

### OPTICAL RESULTS (MEASURED):





LED Opticus Daisy M L28W2  
 FWHM / FWTM 61.0° / 70.0°  
 Efficiency 82 %  
 Peak intensity 1 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C17051\_DAISY-7X1-SHD-MATT



Light distribution files





LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
 FWHM / FWTM 59.0° / 70.0°  
 Efficiency 90 %  
 Peak intensity 1.2 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C18167\_DAISY-7X1-SHD-MET



Light distribution files



LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
 FWHM / FWTM 59.0° / 69.0°  
 Efficiency 84 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C16872\_DAISY-7X1-SHD




Light distribution files

### OPTICAL RESULTS (MEASURED):

**MST** | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
FWHM / FWTM 59.0° / 69.0°  
Efficiency 83 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17051\_DAISY-7X1-SHD-MATT



Light distribution files

**MST** | *Your solutions*



LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
FWHM / FWTM 59.0° / 69.0°  
Efficiency 89 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17533\_DAISY-7X1-SHD-MET-MATT



Light distribution files

**MST** | *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
FWHM / FWTM 59.0° / 69.0°  
Efficiency 90 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C16876\_DAISY-7X1-SHD-WHT




Light distribution files

### OPTICAL RESULTS (MEASURED):

**MST** | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
 FWHM / FWTM 59.0° / 69.0°  
 Efficiency 90 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C17225\_DAISY-7X1-SHD-WHT-MATT



Light distribution files

**MST** | *Your solutions*



LED LinLED 280x28mm 1600lm 840 4C 21V DAISY 7x1(ZT25)  
 FWHM / FWTM 47.0° / 57.0°  
 Efficiency 90 %  
 Peak intensity 1.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 C16872\_DAISY-7X1-SHD



Light distribution files

**OSRAM**

LED PL-LIN-2000 280x24mm  
 FWHM / FWTM 59.0° / 67.0°  
 Efficiency 83 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C17051\_DAISY-7X1-SHD-MATT




Light distribution files

### OPTICAL RESULTS (MEASURED):

**OSRAM**  
Opto Semiconductors



LED OSCONIQ E 2835  
 FWHM / FWTM 59.0° / 68.0°  
 Efficiency 83 %  
 Peak intensity 1.1 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C17051\_DAISSY-7X1-SHD-MATT



Light distribution files

**SAMSUNG**



LED LM28xB Series  
 FWHM / FWTM 51.0° / 65.0°  
 Efficiency 89 %  
 Peak intensity 1.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 C16872\_DAISSY-7X1-SHD



Light distribution files

**SAMSUNG**

LED LM28xB Series  
 FWHM / FWTM 51.0° / 65.0°  
 Efficiency 92 %  
 Peak intensity 1.5 cd/lm  
 LEDs/each optic 2  
 Light colour/type White  
 Required components:  
 C16876\_DAISSY-7X1-SHD-WHT




Light distribution files

### OPTICAL RESULTS (MEASURED):

#### SAMSUNG



LED LM28xB Series  
FWHM / FWTM 51.0° / 65.0°  
Efficiency 92 %  
Peak intensity 1.5 cd/lm  
LEDs/each optic 2  
Light colour/type White  
Required components:  
C17225\_DAISSY-7X1-SHD-WHT-MATT



Light distribution files

#### SAMSUNG



LED LM28xB Series  
FWHM / FWTM 50.0° / 65.0°  
Efficiency 89 %  
Peak intensity 1.5 cd/lm  
LEDs/each optic 2  
Light colour/type White  
Required components:  
C17051\_DAISSY-7X1-SHD-MATT



Light distribution files






LED LED-St-L28W2c4-xxx-C015-55 (DAISSY-7x1)  
FWHM / FWTM 58.0° / 68.0°  
Efficiency 93 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17225\_DAISSY-7X1-SHD-WHT-MATT






Light distribution files

### OPTICAL RESULTS (MEASURED):




### OPTICAL RESULTS (MEASURED):



### OPTICAL RESULTS (MEASURED):




LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC  
FWHM / FWTM 65.0° / 73.0°  
Efficiency 76 %  
Peak intensity 0.7 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17051\_DAISSY-7X1-SHD-MATT



Light distribution files





LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC  
FWHM / FWTM 64.0° / 72.0°  
Efficiency 76 %  
Peak intensity 0.7 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C16872\_DAISSY-7X1-SHD



Light distribution files



LED PassivePAQ-L-1F35-SSA3-2.7K-840-3-DC  
FWHM / FWTM 65.0° / 75.0°  
Efficiency 87 %  
Peak intensity 0.8 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C16876\_DAISSY-7X1-SHD-WHT




Light distribution files

### OPTICAL RESULTS (MEASURED):

#### TRIDONIC



LED LLE 24x280mm 750lm 8x0 LVD ADV1  
 FWHM / FWTM 60.0° / 69.0°  
 Efficiency 83 %  
 Peak intensity 1 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C17051\_DAISSY-7X1-SHD-MATT



Light distribution files

#### TRIDONIC


LED LLE 24x280mm 750lm 8x0 LVD ADV1  
 FWHM / FWTM 60.0° / 70.0°  
 Efficiency 91 %  
 Peak intensity 1 cd/lm  
 LEDs/each optic 4  
 Light colour/type White  
 Required components:  
 C16876\_DAISSY-7X1-SHD-WHT



Light distribution files

#### TRIDONIC

LED LLE 24x280mm 750lm 8x0 LVD ADV1  
 FWHM / FWTM 60.0° / 69.0°  
 Efficiency 83 %  
 Peak intensity 1 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:  
 C16872\_DAISSY-7X1-SHD





Light distribution files

### OPTICAL RESULTS (MEASURED):

#### TRIDONIC

LED LLE 24x280mm 750lm 8x0 LVD ADV1  
FWHM / FWTM 61.0° / 70.0°  
Efficiency 91 %  
Peak intensity 1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17225\_DAISSY-7X1-SHD-WHT-MATT




Light distribution files

### OPTICAL RESULTS (SIMULATED):




LED J Series 2835  
FWHM / FWTM 58.0° / 72.0°  
Efficiency 87 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C16872\_DAISSY-7X1-SHD



Light distribution files




LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
FWHM / FWTM 60.0° / 72.0°  
Efficiency 85 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17051\_DAISSY-7X1-SHD-MATT



Light distribution files



LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
FWHM / FWTM 59.0° / 72.0°  
Efficiency 89 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C16876\_DAISSY-7X1-SHD-WHT




Light distribution files

### OPTICAL RESULTS (SIMULATED):

**MST** | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
FWHM / FWTM 60.0° / 72.0°  
Efficiency 88 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17533\_DAISSY-7X1-SHD-MET-MATT



Light distribution files

**MST** | *Your solutions*


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
FWHM / FWTM 60.0° / 72.0°  
Efficiency 85 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C16872\_DAISSY-7X1-SHD



Light distribution files

**MST** | *Your solutions*

LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
FWHM / FWTM 60.0° / 72.0°  
Efficiency 89 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17225\_DAISSY-7X1-SHD-WHT-MATT




Light distribution files

### OPTICAL RESULTS (SIMULATED):

**MST** | Your solutions


LED LinLED 280x28mm 1100lm 8x0 2C 42V DAISY-7X1 G1  
FWHM / FWTM 59.0° / 72.0°  
Efficiency 88 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C18167\_DAISSY-7X1-SHD-MET



Light distribution files

**OSRAM**  
Opto Semiconductors


LED Duris E 2835  
FWHM / FWTM 57.0° / 72.0°  
Efficiency 90 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17225\_DAISSY-7X1-SHD-WHT-MATT



Light distribution files

**OSRAM**  
Opto Semiconductors

LED Duris E 2835  
FWHM / FWTM 56.0° / 72.0°  
Efficiency 87 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C17051\_DAISSY-7X1-SHD-MATT



Light distribution files


### OPTICAL RESULTS (SIMULATED):

#### SAMSUNG

LED LM28xB Series  
FWHM / FWTM 50.0° / 66.0°  
Efficiency 91 %  
Peak intensity 1.5 cd/lm  
LEDs/each optic 2  
Light colour/type White

Required components:

C17533\_DAISSY-7X1-SHD-MET-MATT




Light distribution files

#### SAMSUNG

LED LM28xB Series  
FWHM / FWTM 50.0° / 66.0°  
Efficiency 92 %  
Peak intensity 1.6 cd/lm  
LEDs/each optic 2  
Light colour/type White

Required components:

C18167\_DAISSY-7X1-SHD-MET




Light distribution files

#### SAMSUNG

LED LM28xB Series  
FWHM / FWTM 56.0° / 70.0°  
Efficiency 85 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White

Required components:

C16872\_DAISSY-7X1-SHD




Light distribution files

### OPTICAL RESULTS (SIMULATED):

#### SAMSUNG


LED LM301B  
FWHM / FWTM 58.0° / 72.0°  
Efficiency 87 %  
Peak intensity 1.1 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:  
C16872\_DAISSY-7X1-SHD



Light distribution files



LED SEOUL DC 3030C  
FWHM / FWTM 57.0° / 72.0°  
Efficiency 88 %  
Peak intensity 1.2 cd/lm  
LEDs/each optic 4  
Light colour/type White  
Required components:  
C16872\_DAISSY-7X1-SHD



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Ledil:](#)

[C16876\\_DAISS-7X1-SHD-WHT](#) [C16989\\_DAISS-7X1-W2](#) [C17051\\_DAISS-7X1-SHD-MATT](#) [C17225\\_DAISS-7X1-SHD-WHT-MATT](#) [C17532\\_DAISS-7X1-SHD-MET](#) [C17533\\_DAISS-7X1-SHD-MET-MATT](#) [C16872\\_DAISS-7X1-SHD](#)