



REVISIONS	
ISSUE	CHANGES
0	ER 8489 CRS 28 APR 70
1	FORMAT CN 10987C J.G.L. 7 APR 72
2	CN 11246A CC 20 JUN 72
3	CN 12912A JL 7 NOV 73
4	CN 24955C M.A. 17 AUG 83

NOTES:

1. FOR USE WITH RG-58 & 141/11 CABLE.
2. FOR CABLING INSTRUCTIONS SEE CP-441.
3. FOR CABLE TRIMMING USE KTJ-72 AND KTD-136
4. FOR CRIMPING USE DIE SIZE G1.

ITEM	REQ'D	DESCRIPTION	DRAWING NO.
8	1	SHV CRIMP CONTACT M	
7	1	HEX. NUT	492A-9-M06
6	1	RETAINING RING	
5	1	LOCKWASHER	492A-12-M06
4	1	GASKET	492A-10-M99
3	1	INSULATOR	
2	1	K-GRIP BODY	
1	1	W/PK-GRIP SLEEVE	C-19-126-B-M06

UNLESS OTHERWISE SPECIFIED:

1. TOLERANCES: FRACTIONS & 2 PLACE DECIMALS ± .010
3 PLACE DECIMALS ± .004
T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES.
2. REMOVE ALL BURRS. BREAK SHARP EDGES .003 MAX.
3. NO FILLETS PERMITTED.
4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX.
5. ALL DIMENSIONS PRIOR TO PLATING.

REF:	NBS. ND-545C
FINISH	
SPEC.	KER-10004
MATL.	
SPEC.	
SHV BULKHEAD JACK	
DRAWN	JCA DATE 3 NOV 89
APPR.	MJB DATE 7 NOV 89
KINGS ELECTRONICS 40 MARLBOROUGH ROAD TUCKAHOE, N. Y. 10707	
DRAWING NO. 1702-2	