

3001

1 Watt - 28 Volts, Class C
Microwave 3000 MHz

GENERAL DESCRIPTION

The 3001 is a COMMON BASE transistor capable of providing 1 Watts Class C, RF output power at 3000 MHz. Gold metalization and diffused ballasting are used to provide high reliability and supreme ruggedness. The transistor uses a fully hermetic High Temperature Solder Sealed package.

ABSOLUTE MAXIMUM RATINGS

Maximum Power Dissipation @ 25°C 5 Watts

Maximum Voltage and Current

BVces Collector to Emitter Voltage 50 Volts

BVebo Emitter to Base Voltage 3.5 Volts


Ic Collector Current 0.20 A

Maximum Temperatures

Storage Temperature - 65 to + 200°C

Operating Junction Temperature + 200°C

CASE OUTLINE 55BT, STYLE 1



ELECTRICAL CHARACTERISTICS @ 25 °C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
P _{out}	Power Out	F = 3.0 GHz	1.0			Watt
P _{in}	Power Input	V _{cb} = 28 Volts		.14	0.2	Watt
P _g	Power Gain	P _o = 1 Watts	7.0	8.5		dB
η _c	Collector Efficiency	As Above		30		%
VSWR ₁	Load Mismatch Tolerance	F = 3 GHz, P _o = 1 W			30:1	


BVces	Collector to Emitter Breakdown	Ic = 10 mA	50			Volts
BVcbo	Collector to Base Breakdown	Ic = 1 mA	45			Volts
BVebo	Emitter to Base Breakdown	Ie = 1 mA	3.5			Volts
Icbo	Collector to Base Current	Vcb = 28 Volts			0.5	mA
h _{FE}	Current Gain	Vce = 5 V, Ic = 100 mA	10			
Cob	Output Capacitance	F = 1 MHz, Vcb = 28 V			35	°C/W
θjc	Thermal Resistance					

Issue August 1996


GHz TECHNOLOGY INC. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. GHz RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.

GHz Technology Inc. 3000 Oakmead Village Drive, Santa Clara, CA 95051-0808 Tel. 408 / 986-8031 Fax 408 / 986-8120


POWER OUTPUT VS FREQUENCY



EFFICIENCY VS FREQUENCY




Pout VS Pin VS FREQUENCY




SMITH CHART
3001

NORMALIZED IMPEDANCE AND ADMITTANCE COORDINATES




NORMALIZED TO A 50 OHM SYSTEM.



FREQUENCY MHz	R	Z _{in} JX	FREQUENCY MHz	R	Z _{load} JX
1.5	15	14	1.5	6	25
2.0	16	20	2.0	5	15
2.3	17	27	2.3	4.5	10
3.0	19	32	3.0	4	0

REVISIONS


ZONE	REV	DESCRIPTION	DATE	APPROVED
------	-----	-------------	------	----------



DIM	INCHES
A	.200
B	.250
C	1.000
D	.500
E	.200
F	.200
G	.500
H	.175
I	.050

3001 TEST AMPLIFIER

f = 3000 MHz



— = Microstrip on 0.020" Teflon Fiberglass, Er=2.55
 C1,C2 = ATC 'A' 47pf
 C3 = 10μfd @ 35 Volts



CAGE OPJR2	DWG NO. 3001	REV A
SCALE 1/1	SHEET	