

DATA SHEET

74LVC4245A

Octal dual supply translating
transceiver; 3-state

Product specification
Supersedes data of 2004 Feb 11

2004 Mar 30

Octal dual supply translating transceiver; 3-state

74LVC4245A

FEATURES

- 5 V tolerant inputs/outputs for interfacing with 5 V logic
- Wide supply voltage range:
 - 3 V port (V_{CCB}): 1.5 V to 3.6 V
 - 5 V port (V_{CCA}): 1.5 V to 5.5 V.
- CMOS low power consumption
- Direct interface with TTL levels
- Inputs accept voltages up to 5.5 V
- High-impedance when $V_{CC} = 0$ V
- Complies with JEDEC standard no. JESD8B/JESD36
- ESD protection:
 - HBM EIA/JESD22-A114-B exceeds 2000 V
 - MM EIA/JESD22-A115-A exceeds 200 V.
- Specified from -40°C to $+85^{\circ}\text{C}$ and -40°C to $+125^{\circ}\text{C}$.

DESCRIPTION

The 74LVC4245A is a high-performance, low-power, low-voltage, Si-gate CMOS device, superior to most advanced CMOS compatible TTL families.

The 74LVC4245A is an octal dual supply translating transceiver featuring non-inverting 3-state bus compatible outputs in both send and receive directions. It is designed to interface between a 3 V and 5 V bus in a mixed 3 V and 5 V supply environment.

The 74LVC4245A features an output enable input (pin $\overline{\text{OE}}$) for easy cascading and a send/receive input (pin DIR) for direction control. Pin $\overline{\text{OE}}$ controls the outputs so that the buses are effectively isolated.

In suspend mode, when V_{CCA} is zero, there will be no current flow from one supply to the other supply. The A-outputs must be set 3-state and the voltage on the A-bus must be smaller than V_{diode} (typical 0.7 V). $V_{CCA} \geq V_{CCB}$ (except in suspend mode).

QUICK REFERENCE DATA

GND = 0 V; $T_{\text{amb}} = 25^{\circ}\text{C}$; $t_r = t_f \leq 2.5$ ns.

SYMBOL	PARAMETER	CONDITIONS	TYPICAL	UNIT
t_{PHL}	propagation delay An to Bn	$C_L = 50$ pF; $V_{CCA} = 5.0$ V; $V_{CCB} = 3.3$ V	3.3	ns
	propagation delay Bn to An	$C_L = 50$ pF; $V_{CCA} = 5.0$ V; $V_{CCB} = 3.3$ V	3.4	ns
t_{PLH}	propagation delay An to Bn	$C_L = 50$ pF; $V_{CCA} = 5.0$ V; $V_{CCB} = 3.3$ V	2.8	ns
	propagation delay Bn to An	$C_L = 50$ pF; $V_{CCA} = 5.0$ V; $V_{CCB} = 3.3$ V	3.0	ns
C_I	input capacitance		4.0	pF
$C_{I/O}$	input/output capacitance An and Bn		5.0	pF
C_{PD}	5 V port: power dissipation capacitance Bn to An	$V_{CC} = 5.0$ V; notes 1 and 2		
		outputs enabled	17	pF
		outputs disabled	5	pF
	3 V port: power dissipation capacitance An to Bn	$V_{CC} = 3.3$ V; notes 1 and 2		
		outputs enabled	17	pF
		outputs disabled	5	pF

Notes

1. C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$$P_D = C_{\text{PD}} \times V_{\text{CC}}^2 \times f_i \times N + \Sigma(C_L \times V_{\text{CC}}^2 \times f_o) \text{ where:}$$

f_i = input frequency in MHz;

f_o = output frequency in MHz;

C_L = output load capacitance in pF;

V_{CC} = supply voltage in Volts;

N = total load switching outputs;

$\Sigma(C_L \times V_{\text{CC}}^2 \times f_o)$ = sum of the outputs.

2. The condition is $V_I = \text{GND to } V_{\text{CC}}$.

Octal dual supply translating transceiver; 3-state

74LVC4245A

FUNCTION TABLE

See note 1.

INPUT		INPUT/OUTPUT	
$\overline{\text{OE}}$	DIR	A _n	B _n
L	L	A = B	input
L	H	input	B = A
H	X	Z	Z

Note

1. H = HIGH voltage level;
L = LOW voltage level;
X = don't care;
Z = high-impedance OFF-state.

ORDERING INFORMATION

TYPE NUMBER	TEMPERATURE RANGE	PACKAGE			
		PINS	PACKAGE	MATERIAL	CODE
74LVC4245AD	−40 °C to +125 °C	24	SO24	plastic	SOT137-1
74LVC4245ADB	−40 °C to +125 °C	24	SSOP24	plastic	SOT340-1
74LVC4245APW	−40 °C to +125 °C	24	TSSOP24	plastic	SOT355-1

PINNING

PIN	SYMBOL	DESCRIPTION
1	V _{CCA}	supply voltage (5 V bus)
2	DIR	direction control
3	A0	data input or output
4	A1	data input or output
5	A2	data input or output
6	A3	data input or output
7	A4	data input or output
8	A5	data input or output
9	A6	data input or output
10	A7	data input or output
11	GND	ground (0 V)
12	GND	ground (0 V)

PIN	SYMBOL	DESCRIPTION
13	GND	ground (0 V)
14	B7	data output or input
15	B6	data output or input
16	B5	data output or input
17	B4	data output or input
18	B3	data output or input
19	B2	data output or input
20	B1	data output or input
21	B0	data output or input
22	$\overline{\text{OE}}$	output enable input (active LOW)
23	V _{CCB}	supply voltage (3 V bus)
24	V _{CCB}	supply voltage (3 V bus)

Octal dual supply translating transceiver; 3-state

74LVC4245A




Fig.1 Pin configuration.




Fig.2 IEC logic symbol.




Fig.3 Logic diagram.

Octal dual supply translating transceiver; 3-state

74LVC4245A

RECOMMENDED OPERATING CONDITIONS

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{CCA}	supply voltage 5 V port (for maximum speed performance)	$V_{CCA} \geq V_{CCB}$; see Fig.4	1.5	5.5	V
V_{CCB}	supply voltage 3 V port (for low-voltage applications)	$V_{CCA} \geq V_{CCB}$; see Fig.4	1.5	3.6	V
V_I	input voltage (control inputs)		0	5.5	V
V_O	output voltage	output HIGH or LOW state	0	V_{CC}	V
		output 3-state	0	5.5	V
T_{amb}	operating ambient temperature		-40	+125	°C
t_r, t_f	input rise and fall times	$V_{CCB} = 2.7 \text{ V to } 3.0 \text{ V}$	0	20	ns/V
		$V_{CCB} = 3.0 \text{ V to } 3.6 \text{ V}$	0	10	ns/V
		$V_{CCA} = 3.0 \text{ V to } 4.5 \text{ V}$	0	20	ns/V
		$V_{CCA} = 4.5 \text{ V to } 5.5 \text{ V}$	0	10	ns/V

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 60134); voltages are referenced to GND (ground = 0 V).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{CCA}	supply voltage 5 V port		-0.5	+6.5	V
V_{CCB}	supply voltage 3 V port		-0.5	+4.6	V
I_{IK}	input diode current	$V_I < 0 \text{ V}$	-	-50	mA
V_I	input voltage	note 1	-0.5	+6.5	V
I_{OK}	output diode current	$V_O > V_{CC}$ or $V_O < 0 \text{ V}$	-	±50	mA
V_O	output voltage	output HIGH or LOW state; note 1	-0.5	$V_{CC} + 0.5$	V
		output 3-state; note 1	-0.5	+6.5	V
I_O	output source or sink current	$V_O = 0 \text{ V to } V_{CC}$	-	±50	mA
I_{CC}, I_{GND}	V_{CC} or GND current		-	±100	mA
T_{stg}	storage temperature		-65	+150	°C
P_{tot}	power dissipation	$T_{amb} = -40 \text{ °C to } +125 \text{ °C}$; note 2	-	500	mW

Notes

1. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.
2. For SO24 packages: above 70 °C the value of P_{tot} derates linearly with 8 mW/K.
For (T)SSOP24 packages: above 60 °C the value of P_{tot} derates linearly with 5.5 mW/K.

Octal dual supply translating transceiver; 3-state

74LVC4245A

DC CHARACTERISTICS

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

SYMBOL	PARAMETER	TEST CONDITIONS			MIN.	TYP.	MAX.	UNIT
		OTHER	V _{CCA} (V)	V _{CCB} (V)				
T _{amb} = −40 °C to +85 °C; note 1								
V _{IH}	HIGH-level input voltage		–	2.7 to 3.6	2.0	–	–	V
			4.5 to 5.5	–	2.0	–	–	V
V _{IL}	LOW-level input voltage		–	2.7 to 3.6	–	–	0.8	V
			4.5 to 5.5	–	–	–	0.8	V
V _{OH}	HIGH-level output voltage	V _I = V _{IH} or V _{IL} I _O = −12 mA I _O = −100 μA I _O = −24 mA	–	2.7	V _{CCB} − 0.5	–	–	V
			–	2.7 to 3.6	V _{CCB} − 0.2	V _{CCB}	–	V
			–	3.0	V _{CCB} − 0.8	–	–	V
		V _I = V _{IH} or V _{IL} I _O = −12 mA I _O = −100 μA I _O = −24 mA	4.5	–	V _{CCA} − 0.5	–	–	V
			4.5 to 5.5	–	V _{CCA} − 0.2	V _{CCA}	–	V
			4.5	–	V _{CCA} − 0.8	–	–	V
V _{OL}	LOW-level output voltage	V _I = V _{IH} or V _{IL} I _O = 12 mA I _O = 100 μA I _O = 24 mA	–	2.7	–	–	0.40	V
			–	2.7 to 3.6	–	–	0.20	V
			–	3.0	–	–	0.55	V
		V _I = V _{IH} or V _{IL} I _O = 12 mA I _O = 100 μA I _O = 24 mA	4.5	–	–	–	0.40	V
			4.5 to 5.5	–	–	–	0.20	V
			4.5	–	–	–	0.55	V
I _{LI}	input leakage current	V _I = 5.5 V or GND	–	–	–	±0.1	±5	μA
I _{OZ}	3-state output OFF-state current	V _I = V _{IH} or V _{IL} ; V _O = V _{CC} or GND; note 2	–	3.6	–	±0.1	±5	μA
			5.5	–	–	±0.1	±5	μA
I _{CC}	quiescent supply current	V _I = V _{CC} or GND; I _O = 0 A	–	3.6	–	0.1	10	μA
			5.5	–	–	0.1	10	μA
ΔI _{CC}	additional quiescent supply current per control pin	V _I = V _{CC} − 0.6 V; I _O = 0 A; note 3	–	2.7 to 3.6	–	5	500	μA
			4.5 to 5.5	–	–	5	500	μA

Octal dual supply translating transceiver; 3-state

74LVC4245A

SYMBOL	PARAMETER	TEST CONDITIONS			MIN.	TYP.	MAX.	UNIT
		OTHER	V _{CCA} (V)	V _{CCB} (V)				
T _{amb} = −40 °C to +125 °C								
V _{IH}	HIGH-level input voltage		–	2.7 to 3.6	2.0	–	–	V
			4.5 to 5.5	–	2.0	–	–	V
V _{IL}	LOW-level input voltage		–	2.7 to 3.6	–	–	0.8	V
			4.5 to 5.5	–	–	–	0.8	V
V _{OH}	HIGH-level output voltage	V _I = V _{IH} or V _{IL} I _O = −12 mA I _O = −100 μA I _O = −24 mA	–	2.7	V _{CCB} − 0.65	–	–	V
			–	2.7 to 3.6	V _{CCB} − 0.3	–	–	V
			–	3.0	V _{CCB} − 1.0	–	–	V
		V _I = V _{IH} or V _{IL} I _O = −12 mA I _O = −100 μA I _O = −24 mA	4.5	–	V _{CCA} − 0.65	–	–	V
			4.5 to 5.5	–	V _{CCA} − 0.3	–	–	V
			4.5	–	V _{CCA} − 1.0	–	–	V
V _{OL}	LOW-level output voltage	V _I = V _{IH} or V _{IL} I _O = 12 mA I _O = 100 μA I _O = 24 mA	–	2.7	–	–	0.60	V
			–	2.7 to 3.6	–	–	0.30	V
			–	3.0	–	–	0.80	V
		V _I = V _{IH} or V _{IL} I _O = 12 mA I _O = 100 μA I _O = 24 mA	4.5	–	–	–	0.60	V
			4.5 to 5.5	–	–	–	0.30	V
			4.5	–	–	–	0.80	V
I _{LI}	input leakage current	V _I = 5.5 V or GND	–	–	–	–	±20	μA
I _{OZ}	3-state output OFF-state current	V _I = V _{IH} or V _{IL} ; V _O = V _{CC} or GND; note 2	–	3.6	–	–	±20	μA
			5.5	–	–	–	±20	μA
I _{CC}	quiescent supply current	V _I = V _{CC} or GND; I _O = 0 A	–	3.6	–	–	40	μA
			5.5	–	–	–	40	μA
ΔI _{CC}	additional quiescent supply current per control pin	V _I = V _{CC} − 0.6 V; I _O = 0 A; note 3	–	2.7 to 3.6	–	–	5000	μA
			4.5 to 5.5	–	–	–	5000	μA

Notes

1. All typical values are at $V_{CCA} = 5.0\text{ V}$, $V_{CCB} = 3.3\text{ V}$ and $T_{amb} = 25\text{ }^{\circ}\text{C}$.
2. For transceivers, the parameter I_{OZ} includes the input leakage current.
3. $V_{CCB} = 2.7\text{ V to }3.6\text{ V}$: other inputs at V_{CCB} or GND.
 $V_{CCA} = 4.5\text{ V to }5.5\text{ V}$: other inputs at V_{CCA} or GND.

Octal dual supply translating transceiver; 3-state

74LVC4245A

AC CHARACTERISTICS

GND = 0 V; $V_{CCA} = 4.5\text{ V to }5.5\text{ V}$; $t_r = t_f \leq 2.5\text{ ns}$; $C_L = 50\text{ pF}$.

SYMBOL	PARAMETER	CONDITIONS		MIN.	TYP.	MAX.	UNIT
		WAVEFORMS	V _{CCB} (V)				
T _{amb} = −40 °C to +85 °C; note 1							
t _{PHL}	propagation delay An to Bn	see Figs 5 and 7	2.7	1.0	3.6	6.3	ns
			3.0 to 3.6	1.0	3.3 ⁽²⁾	6.3	ns
	propagation delay Bn to An		2.7	1.0	3.4	6.1	ns
			3.0 to 3.6	1.0	3.4 ⁽²⁾	6.1	ns
t _{PLH}	propagation delay An to Bn		2.7	1.0	3.3	6.7	ns
			3.0 to 3.6	1.0	2.8 ⁽²⁾	6.5	ns
	propagation delay Bn to An		2.7	1.0	3.0	5.0	ns
			3.0 to 3.6	1.0	3.0 ⁽²⁾	5.0	ns
t _{PZL}	3-state output enable time $\overline{OE}$ to An	see Figs 6 and 7	2.7	1.0	4.5	9.0	ns
			3.0 to 3.6	1.0	4.5 ⁽²⁾	9.0	ns
	3-state output enable time $\overline{OE}$ to Bn		2.7	1.0	4.4	8.7	ns
			3.0 to 3.6	1.0	3.8 ⁽²⁾	8.1	ns
t _{PZH}	3-state output enable time $\overline{OE}$ to An		2.7	1.0	4.5	8.1	ns
			3.0 to 3.6	1.0	4.5 ⁽²⁾	8.1	ns
	3-state output enable time $\overline{OE}$ to Bn		2.7	1.0	4.3	8.7	ns
			3.0 to 3.6	1.0	3.2 ⁽²⁾	8.1	ns
t _{PLZ}	3-state output disable time $\overline{OE}$ to An	see Figs 6 and 7	2.7	1.0	2.9	7.0	ns
			3.0 to 3.6	1.0	2.9 ⁽²⁾	7.0	ns
	3-state output disable time $\overline{OE}$ to Bn		2.7	1.0	3.9	7.7	ns
			3.0 to 3.6	1.0	3.5 ⁽²⁾	7.7	ns
t _{PHZ}	3-state output disable time $\overline{OE}$ to An		2.7	1.0	2.8	5.8	ns
			3.0 to 3.6	1.0	2.8 ⁽²⁾	5.8	ns
	3-state output disable time $\overline{OE}$ to Bn		2.7	1.0	3.3	7.8	ns
			3.0 to 3.6	1.0	2.9 ⁽²⁾	7.8	ns
t _{sk(0)}	skew	note 3		—	—	1.0	ns

Octal dual supply translating transceiver; 3-state

74LVC4245A

SYMBOL	PARAMETER	CONDITIONS		MIN.	TYP.	MAX.	UNIT
		WAVEFORMS	V _{CCB} (V)				
T _{amb} = −40 °C to +125 °C							
t _{PHL}	propagation delay An to Bn	see Figs 5 and 7	2.7	1.0	–	8.0	ns
			3.0 to 3.6	1.0	–	8.0	ns
	propagation delay Bn to An		2.7	1.0	–	8.0	ns
			3.0 to 3.6	1.0	–	8.0	ns
t _{PLH}	propagation delay An to Bn		2.7	1.0	–	8.5	ns
			3.0 to 3.6	1.0	–	8.5	ns
	propagation delay Bn to An		2.7	1.0	–	6.5	ns
			3.0 to 3.6	1.0	–	6.5	ns
t _{PZL}	3-state output enable time $\overline{OE}$ to An	see Figs 6 and 7	2.7	1.0	–	11.5	ns
			3.0 to 3.6	1.0	–	11.5	ns
	3-state output enable time $\overline{OE}$ to Bn		2.7	1.0	–	11.0	ns
			3.0 to 3.6	1.0	–	10.5	ns
t _{PZH}	3-state output enable time $\overline{OE}$ to An		2.7	1.0	–	10.5	ns
			3.0 to 3.6	1.0	–	10.5	ns
	3-state output enable time $\overline{OE}$ to Bn		2.7	1.0	–	11.0	ns
			3.0 to 3.6	1.0	–	10.5	ns
t _{PLZ}	3-state output disable time $\overline{OE}$ to An	see Figs 6 and 7	2.7	1.0	–	9.0	ns
			3.0 to 3.6	1.0	–	9.0	ns
	3-state output disable time $\overline{OE}$ to Bn		2.7	1.0	–	10.0	ns
			3.0 to 3.6	1.0	–	10.0	ns
t _{PHZ}	3-state output disable time $\overline{OE}$ to An		2.7	1.0	–	7.5	ns
			3.0 to 3.6	1.0	–	7.5	ns
	3-state output disable time $\overline{OE}$ to Bn		2.7	1.0	–	10.0	ns
			3.0 to 3.6	1.0	–	10.0	ns
t _{sk(0)}	skew	note 3		–	–	1.5	ns

Notes

1. Typical values are measured at V_{CCA} = 5.0 V and T_{amb} = 25 °C.
2. Typical values measured at V_{CCB} = 3.3 V.
3. Skew between any two outputs of the same package switching in the same direction. This parameter is guaranteed by design.

Octal dual supply translating transceiver;
3-state

74LVC4245A

AC WAVEFORMS





Fig.4 Supply operation area.





$V_M = 1.5\text{ V}$ at $2.7\text{ V} \leq V_{CCB} \leq 3.6\text{ V}$;
 $V_M = 0.5V_{CCA}$ at $V_{CCA} \geq 4.5\text{ V}$;
 V_{OL} and V_{OH} are typical output voltage drop that occur with the output load.

Fig.5 Input (An, Bn) to output (Bn, An) propagation delays.

Octal dual supply translating transceiver;
3-state

74LVC4245A




Octal dual supply translating transceiver; 3-state

74LVC4245A

PACKAGE OUTLINES

SO24: plastic small outline package; 24 leads; body width 7.5 mm

SOT137-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

UNIT	A max.	A ₁	A ₂	A ₃	b _p	c	D ⁽¹⁾	E ⁽¹⁾	e	H _E	L	L _p	Q	v	w	y	z ⁽¹⁾	θ
mm	2.65	0.3 0.1	2.45 2.25	0.25	0.49 0.36	0.32 0.23	15.6 15.2	7.6 7.4	1.27	10.65 10.00	1.4	1.1 0.4	1.1 1.0	0.25	0.25	0.1	0.9 0.4	8° 0°
inches	0.1	0.012 0.004	0.096 0.089	0.01	0.019 0.014	0.013 0.009	0.61 0.60	0.30 0.29	0.05	0.419 0.394	0.055	0.043 0.016	0.043 0.039	0.01	0.01	0.004	0.035 0.016	

Note
1. Plastic or metal protrusions of 0.15 mm (0.006 inch) maximum per side are not included.


OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT137-1	075E05	MS-013				99-12-27 03-02-19

Octal dual supply translating transceiver; 3-state

74LVC4245A

SSOP24: plastic shrink small outline package; 24 leads; body width 5.3 mm

SOT340-1



DIMENSIONS (mm are the original dimensions)

UNIT	A max.	A ₁	A ₂	A ₃	b _p	c	D ⁽¹⁾	E ⁽¹⁾	e	H _E	L	L _p	Q	v	w	y	z ⁽¹⁾	θ
mm	2	0.21 0.05	1.80 1.65	0.25	0.38 0.25	0.20 0.09	8.4 8.0	5.4 5.2	0.65	7.9 7.6	1.25	1.03 0.63	0.9 0.7	0.2	0.13	0.1	0.8 0.4	8° 0°

Note
1. Plastic or metal protrusions of 0.2 mm maximum per side are not included.


OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT340-1		MO-150				99-12-27 03-02-19

Octal dual supply translating transceiver; 3-state

74LVC4245A

TSSOP24: plastic thin shrink small outline package; 24 leads; body width 4.4 mm

SOT355-1



DIMENSIONS (mm are the original dimensions)

UNIT	A _{max.}	A ₁	A ₂	A ₃	b _p	c	D ⁽¹⁾	E ⁽²⁾	e	H _E	L	L _p	Q	v	w	y	Z ⁽¹⁾	θ
mm	1.1	0.15 0.05	0.95 0.80	0.25	0.30 0.19	0.2 0.1	7.9 7.7	4.5 4.3	0.65	6.6 6.2	1	0.75 0.50	0.4 0.3	0.2	0.13	0.1	0.5 0.2	8° 0°

Notes

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.
2. Plastic interlead protrusions of 0.25 mm maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT355-1		MO-153				99-12-27 03-02-19

Octal dual supply translating transceiver; 3-state

74LVC4245A

DATA SHEET STATUS

LEVEL	DATA SHEET STATUS ⁽¹⁾	PRODUCT STATUS ⁽²⁾⁽³⁾	DEFINITION
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

Notes

1. Please consult the most recently issued data sheet before initiating or completing a design.
2. The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.
3. For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

DEFINITIONS

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

DISCLAIMERS

Life support applications — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

Philips Semiconductors – a worldwide company

Contact information

For additional information please visit <http://www.semiconductors.philips.com>. Fax: **+31 40 27 24825**

For sales offices addresses send e-mail to: sales.addresses@www.semiconductors.philips.com.

© Koninklijke Philips Electronics N.V. 2004

SCA76

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

R20/05/pp16

Date of release: 2004 Mar 30

Document order number: 9397 750 13036

Let's make things better.

**Philips
Semiconductors**



PHILIPS