



What can we help you find?

- [Products](#)
- [Industries](#)
- [Resources](#)
- [About TE](#)
- [My Account](#)
- [Innovation](#)
- [Support Center](#)

**1206SFF500F/32-2 Product Details**

- [Share](#) [Print](#) [Email](#)



**1206SFF500F/32-2**

TE Internal Number: F10326-000  
✔ Active

**Fuses**

✔ Always EU RoHS/ELV Compliant (Statement of Compliance)

**Product Highlights:**

- Type = DC Fast Acting Chip Fuse
- Surface Mount Construction
- Form Factor (inches) = 1206
- Form Factor (mm) = 3216
- Rated Current = 5 A

[View all Features](#)

**Quick Links**

- [▶ Check Pricing & Availability](#)
- [▶ Search for Tooling](#)
- [▶ Product Feature Selector](#)
- [▶ Contact Us About This Product](#)

- [Add to My Part List](#)   
 [Request Sample](#)   
 [Find Similar Products](#)   
 [Buy Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- None Available

**Catalog Pages/Data Sheets:**

- [CP CATALOG 2011-FUSES](#) (PDF, English)

**Product Specifications:**

- [12006SFF FAMILY](#) (PDF, English)

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files:**

- None Available

**Related Products:**

- [Tooling](#)

[List all Documents](#)

**Product Features (Please use the Product Drawing for all design activity)**

**Product Type Features:**

- Family Name = SFF
- UL Listed = File No. E197536

**Electrical Characteristics:**

- Rated Current (A) = 5
- Cold DCR (Nominal) (Ω) = 0.015
- Interrupt Voltage, Max. (VDC) = 32
- Interrupt Current, Max. (A) = 45

**Termination Features:**

- Construction = Surface Mount

**Body Features:**

- Type = DC Fast Acting Chip Fuse

**Configuration Features:**

- Form Factor (inches) = 1206
- Form Factor (mm) = 3216

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

**Environmental:**

- Operating Temperature (Max.) (°C) = 125

**Conditions for Usage:**

- Min Clear Time @ 100% Rated Current (Hr) = 4
- Max Clear Time @ 250% Rated Current (Seconds) = 5
- Max Clear Time @ 400% Rated Current (Seconds) = 0.05

**Other:**

- Brand = Raychem

**Corporate Information**

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

**Quick Links**

- [Check Distributor Inventory](#)
- [Cross Reference Products](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

**Customer Support**

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)

**Keep Me Informed**

Receive TE News, Events &  
Technology Updates

Enter your email address

