**Heatsinks f.cool**

- Profile heatsinks and fluid coolers
  - Standard extruded heatsinks
  - Extruded heatsinks for lock-in retaining spring
  - Extruded heatsinks for PCB mounting
  - Extruded heatsinks for DC/DC converter
  - Retaining springs for transistors
  - U-Extruded heatsinks
  - Die-cast heatsinks
  - Fin coolers
  - Fluid coolers
  - Aluminium flat-, quadrangular-, angled-, U- & T-profiles
- Heatsinks and active heatsinks for processors
- Finger shapes heatsinks and small heatsinks
- Cooling aggregates
- Accessories for electronic components

**Cases f.case**

**Connectors f.con**

## Extruded heatsinks for PCB mounting

### SK 129 25,4 STC

42 x 25 mm, for semiconductor clip-mounting

add to request

Features | Technical Drawing | Variants | Service | Accessories / related products

| | |
|---|---|
| **way of fixation** | Clip-Befestigung |
| **heigth** | 25 mm |
| **plate thickness** | 1.8 mm |
| **lengths** | 25.4 mm |
| **$R_{th}$** | 7.8 K/W |
| **drilling pattern** | TO 220 |
| **mouting method** | with solder pin |
| **surface** | black anodised |

Fischer Elektronik GmbH & Co. KG
Nottebohmstraße 28, D - 58511 Lüdenscheid
+49 (0) 23 51 / 4 35 - 0, info@fischerelektronik.de