- Heatsinks f.cool
- Cases f.case
- Connectors f.con
  - Sockets
  - PCB connectors
    - Male headers
    - Female headers
    - Direct female connector
    - Jumpers
  - IDC-connectors
  - D-Sub connectors
  - Brackets for PC
  - Optoelectronics

Female headers

BL 1 14 G

Stamped contact spring (fork contact), for □ 0.635 mm
V-notches permit breaking! Therefore any required number of contacts is available.

add to request

Features | Technical Drawing | Accessories / related products

no. of contacts	14
contact material	CuSn-Legierung
surface contact /	Ni+0,2µm Au
contact sleeve	Ni+4...6µm Sn
surface of contact	gold-plated
Typ Innenfeder	Gabelkontakt
plugability	□ 0,5 mm bis □ 0,7 mm
insertion depth	1,5 ... 5,0 mm
plug-in cross-section	square 0.635
insertion / extraction force	1,5 N / 1,3 N
volume resistivity	≤10 mΩ
capacity between two adjacent contacts	≤ 0,9 pF
nominal current	3 A
nominal voltage	125 V AC
test voltage	1500 V
material isolation body	PPS
temperature range	-40 °C ... +163 °C (260 °C / 10 s)
class of flammibility	UL 94 V-0
insulation resistance	$>10^{12}$ Ω
version	stamped contact spring (fork contact)
connection type	soldering
reflow solderable	yes

Fischer Elektronik GmbH & Co. KG
Nottebohmstraße 28, D - 58511 Lüdenscheid
☎: +49 (0) 23 51 / 4 35 - 0, info@fischerelektronik.de