

► [Heatsinks f.cool](#)

► [Cases f.case](#)

▼ [Connectors f.con](#)

► [Sockets](#)

▼ [PCB connectors](#)

■ [Male headers](#)

■ [Female headers](#)

■ [Direct female connectors](#)

■ [Jumpers](#)

► [IDC-connectors](#)

► [D-Sub connectors](#)

■ [Brackets for PC](#)

► [Optoelectronics](#)

Female headers

BL 2 ...

BL 2 6 G

Stamped contact spring (fork contact), for $\varnothing 0.635$ mm separable! Therefore any required number of contacts is available.

add to request



Features

Technical Drawing

Service

Accessories / related products

no. of contacts	6
contact material	CuSn alloy
surface contact / contact sleeve	Ni+ $\geq 0.2 \mu\text{m}$ Au Ni+4...6 μm Sn
surface of contact	gold-plated
type internal spring	fork contact
plugability for circuit points	$\varnothing 0.5 \dots 0.7$ mm
insert depth	1.5...5 mm
plug-in cross-section	$\varnothing 0.635$ mm
insertion / drawing force	1.5 N/1.3 N
volume resistance	≤ 10 m Ω
capacity between two adjacent contacts	≤ 0.9 pF
nominal current	3 A
nominal voltage	125 V AC
test voltage	1500 V
insulating body material	PPS
temperature range	-40°C... +200°C (260°C/10 s)
class of flammability	UL 94 V-0
version	stamped contact spring (fork contact)
specific insulation resistance	$> 10^{12}$ $\Omega \cdot \text{m}$
connection type	soldering
reflow solderable	yes