

- Heatsinks f.cool
- Cases f.case
- ▼ Connectors f.con
 - Sockets
 - ▼ PCB connectors
 - Male headers
 - Female headers
 - Direct female connectors
 - Jumpers
 - IDC-connectors
 - D-Sub connectors
 - Brackets for PC
 - Optoelectronics

Male headers

SL 13 ...

SL 13 097 10 S
□ 0.635 mm, Sandwich

add to request 



FeaturesTechnical DrawingVariantsServiceAccessories / related products

Article 1-10 of 18

1 | 2 > >>

Number per page: 10

Picture	Name
	►Female headers / BL 1 ... Stamped contact spring (fork contact), for □ 0...
	►Female headers / BL 3 ... Stamped contact spring (fork contact), for □ 0...
	►Female headers / BL LP 1 ... for □ 0.635 mm
	►Female headers / BL LP 3 ... for □ 0.635 mm
	►Female headers / BL 11 ... □ 0.635 mm, can be put through from above and below / 260 °C Reflow
	►Female headers / BL 5 ... for □ 0.635 mm and up to 0.85 mm Ø
	►Female headers / BL 7 ... for □ 0.635 mm and up to 0.85 mm Ø
	►Female headers / MK 21 ... □ 0.635 mm and up to 0.85 mm Ø
	►Female headers / BL 9 ... for □ 0.635 mm and up to 0.85 mm Ø...
	►Female headers / BL 13 ... for □ 0.635 mm and up to 0.85 mm Ø, for PC 104 modules

Article 1-10 of 18

1 | 2 > >>