



DP6020NH-100M

Features

- ▶ SMD Inductor.
- ▶ Resin shielded construction.
- ▶ Compatible with RoHs, Halogen Free and Lead Free.
- ▶ Available tape and reel for auto insertion.

Applications

- ▶ For small DC/DC converter (LCD/LED/OLED DISPLAY, HDD, DSC etc)
- ▶ For power supply circuits




Dimension (Unit:mm)



A	B	H
6.0±0.2	6.0±0.2	2.0Max

Land Pattern (Unit:mm)



L	G	H
6.20	2.80	5.70

Specifications

Part Number	Inductance (uH)	Tolerance	DCR(mohm) ±20%	IDC1(A) Max	IDC2(A) Max	Test Frequency (Hz)
DP6020NH-100M	10	±20%	105	1.90	1.50	100k

- IDC1: When based on the inductance change rate (approximately 30% below in the initial value)
- IDC2: When based on the temperature increase (Temperature increase of approximately 40°C by self heating)

Ilisan Sales Office (KOREA)
 H.K Sales Office (HongKong)
 Shenzhen Sales Office (CHINA)
 LA Sales Office (USA)
 Hungary Sales office (EUROPE)

+82)31-904-1444
 +852)2711-5551
 +0755-8663-6929
 +1)866-446-3586
 +36)30-521-7818

coilmaster@coilmaster.com
coilmaster@coilmaster.com
kimha@coilmaster.com
markyang@coilmaster.com
coilmaster@coilmaster.com