

Data sheet

PT045xxVBEC Typ 019

Page 1/5

P/N


310191xx

xx=number of poles


2021/09/15

Version: S


Illustrations



Dimensional drawing



Drill pattern



See enlarged drawings at the end of document

Product specification

- pin header, solderable
- centerline 5.00 mm, direction of connection vertical 0°
- open ends, fittable without loss of poles
- color black



U | Contact

Data sheet PT045xxVBEC Typ 019

Page 2/5

P/N
310191xx

xx=number of poles

2021/09/15

Version: S

Technical Data

General Data			
Solder pin length	5.2 mm		
min. number of poles	2		
max. number of poles	22		
Insulating material class	CTI 600		
clearance/creepage dist.	3.7 mm		
Protection category	IP00		
Rated current	10 A		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Rated voltage	250 V	630 V	630 V
Rated test voltage	4 kV	4 kV	4 kV

Approvals	
 V / A	300 / 15
approval UL - File No.	E121004
 1.5 mm ²	250 V / 4 kV / 10 A / 1.0 mm

Material	
insulating material	PA66
flammability class	V0
contact pin material	CuZnPb
contact pin surface	Ni + Ag
Glow-Wire Flammability GWFI	960 °C acc. to IEC 60695-2-12
Glow-Wire Flammability GWIT	775 °C acc. to IEC 60695-2-13
REACH - substance (SVHC)	Lead / 7439-92-1

Climatic Data	
upper limit temperature	105 °C
lower limit temperature	-40 °C

general	
Tolerance	ISO 2768 -mH
Solderability	Acc. to JEDEC JESD22-B102E 245°C/5s

U | Contact

Data sheet

Page 3/5

PT045xxVBEC Typ 019

P/N

310191xx**xx=number of poles**

2021/09/15

Version: S

Counterpart of

P/N	Designation
310091	RP015xxWBWC Typ 009
310131	RP035xxIBLN Typ 013
310261	FT085xxVBFC Type 026
310491	RP015xxWBLC Typ 049

U | Contact

Data sheet

PT045xxVBEC Typ 019

Page 4/5

P/N

310191xx


xx=number of poles

2021/09/15

Version: S

Illustrations

Dimensional drawing



$L = (\text{pole size} - 1) \times \text{centerline} + 5 \text{ mm} [0.197]$

U | Contact

Data sheet

PT045xxVBEC Typ 019

Page 5/5

P/N

310191xx

xx=number of poles

2021/09/15

Version: S

Illustrations

Drill pattern

