

Product data sheet

Specifications



Limit switch lever, Limit switches XC Standard, ZCY, spring rod with metal end

ZCY91

Product availability : Stock - Normally stocked in distribution facility

Price* : 6.50 USD

Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch lever
Device short name	ZCY
Product Compatibility	XCKT XCKP XCMD XCKD
Associated head	ZCE01 ZCE05
Movement of operating head	Rotary
Type of operator	Spring rod lever spring return with metal rod)
Tracks	No track
Type of approach	Lateral approach

Complementary

Switch actuation	By any moving part
Positive opening	Without

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22413-LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	T
GTIN	3389110192193
Returnability	Yes
Country of origin	ID

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	6.89 in (17.5 cm)
Number of Units in Package 1	1
Package 1 Width	0.63 in (1.6 cm)
Package 1 Height	0.59 in (1.5 cm)
Package 1 Weight	0.88 oz (25.0 g)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------