



snap switch, 9007CO, plunger head, 2 NO and 2 NC contact, 3 A at 120 VAC, 600 V maximum

9007CO3

Product availability: Stock - Normally stocked in distribution

Price*: 92.00 USD

V	aı	r

Main	
Range of Product	9007
Series name	Heavy duty
Product or Component Type	Snap basic limit switch
Device short name	9007AO/CO
Body type	Fixed

Complementary	
Mounting Mode	-
Operator profile	Plunger head
Material	Metal
Body Material	Cast zinc
Operator material	Cast zinc
Fixing Mode	By the body
Movement of operating head	Linear
Type of operator	Spring return plunger plastic with thermoplastic end
Switch actuation	On end
Type of approach	Vertical approach, 1 direction
Electrical connection	12 6 binder head screw terminals AWG 22AWG 14)
Number of poles	2
Contacts type and composition	2(NC-NO) DPDT-DB
Contact form	Form ZZ
Contact operation	Snap action
Number of steps	1
Contacts material	Silver contacts
Positive opening	Without
Terminals description ISO n°1	(3-4)NO (1-2)NC (5-6)NC (7-8)NO

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Minimum force for tripping

Maximum force for tripping	0.75 lbf
[le] rated operational current	0.6 A 600 V AC, B600 NEMA rating designation 0.75 A 480 V AC, B600 NEMA rating designation 1.5 A 240 V AC, B600 NEMA rating designation 3 A 120 V AC, B600 NEMA rating designation 0.1 A 250 V DC 0.2 A 125 V DC
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	600 V 3)UL 508 contact block 600 VCSA C22.2 No 14 contact block
Width	0.83 in (21.08 mm)
Height	2.5 in (63.50 mm)
Depth	1.14 in (28.96 mm)
Net Weight	0.5 lb(US) (0.23 kg)
Environment NEMA degree of protection IP degree of protection	NEMA 1 Nema type 250 IP20 conforming to IEC 60529
Ambient air temperature for	-20185 °F (-2985 °C)
operation Ambient Air Temperature for Storage	-20185 °F (-2985 °C)
Ordering and shipping o	letails
Category	21492-9007 C SNAP SWITCHES
Discount Schedule	DS1
GTIN	785901821007
Nbr. of units in pkg.	1
Package weight(Lbs)	1.76 oz (49.895 g)
Returnability	Yes

Unit Type of Package 1	PCE
Package 1 Height	0.90 in (2.286 cm)
Package 1 width	2.60 in (6.604 cm)
Package 1 Length	1.20 in (3.048 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

144	40
Warranty	18 months