

3M AGF6200 Anti-Glare Protection Film

Technical Data Sheet

April, 2014

Description 3M™ AGF6200 Anti-Glare Protection Film uses 3M's advanced coating technology to provide durable protection and glare reduction for a clear image with a residue-free, self-wetting adhesive for application on electronic displays.

Applications 3M AGF6200 Anti-Glare Protection Film is typically used to provide display protection and viewing enhancement for electronic displays, especially in environments where bright light conditions can disrupt display readability.

The matte front surface enhances the viewing experience by diffusing mirror-like reflections. The film and coatings are near color-neutral and non-conductive, enabling application to any of today's touch panel technologies. By providing a durable hardcoat barrier between the display surface and the user or environment, this film helps protect against scratches and damage to the display. The residue-free adhesive technology gives an easy-to-apply and easy-to-remove application experience for the user.

Typical Properties

Technical information provided consists of typical developmental product data and should not be used for specification purposes. Unless otherwise noted, all tests are performed at room temperature.

Property	Typical Value	Test Method
Transmission	94%	ASTM D1003-11 ^{E1}
Haze	20%	ASTM D1003-11 ^{E1}
Clarity	40%	ASTM D1003-11 ^{E1}
Gloss (20°, front surface only)	5	ASTM D523-08
Thickness	0.146 mm	ASTM D3652/D3652M-01
Steel Wool Abrasion	Light scratching, 125 g/cm ² , 25 rubs, #0000 steel wool	3M TM-095
Pencil Hardness	3H (500g)	ASTM D3363-05
Chemical resistance	Bleach, MEK, IPA, Acetone, Window Cleaner, Motor Oil, Cola, Coffee, water insoluble marker, water	3M TM-118

Environmental Conditioning	Visual Evaluation
Heat (85°C for 500 hours) Cold (-40°C for 500 hours) Humidity (60°C/90% RH for 500 hours) Thermal shock (85°C to -40°C for 1 hour each, 100 cycles)	No Significant change when observed with the unaided eye

3M AGF6200 Anti-Glare Protection Film

Product Features

- Durable hardcoat for long lasting display protection and the screen protector stays looking good longer
- Anti-glare coating to reduce mirror-like reflections
- Low tack, easy to apply and remove adhesive

Shelf Life & Storage (prior to application)

Material should be stored in its original packaging, laying in a horizontal orientation, away from direct sunlight. Heavy objects should not be placed on top of it to avoid damaging the product. Ambient temperature and humidity should be controlled to 10-30° C at 30-60% relative humidity.

Availability

For availability, please contact our customer service group at 1-800-553-9215 or visit our website at www.3Mscreenprotectors.com

Important Notice

The following is made in lieu of all warranties, express or implied, including any implied warranties of merchantability or fitness for a particular purpose.

3M warrants that, at the time of shipment, product will meet 3M's published specification or that specification agreed in writing between 3M and purchaser. Should product not meet specifications at time of shipment, 3M will replace or refund the purchase price of such quantity of the product found not to meet specifications. Purchaser shall determine the suitability of the 3M Product for purchaser's application. **3M shall not be liable under any legal theory, including in contract or in tort, for any injury, loss, or damage, whether direct, indirect, incidental, special or consequential, arising out of the use of or the inability to use the product.**

The warranties and remedies set forth herein are purchaser's sole and exclusive warranties and remedies.

3M is a trademark of 3M Company

3M
Display Material & Systems Division
Specialty Display Systems
Bldg. 235-1E-54/3M Center
St. Paul, MN 55144-1000
800-553-9215
www.3Mscreenprotectors.com

Please recycle © 3M 2014 All rights reserved
