

## NEW PRODUCTS AVAILABLE IN 2003

### CSCGT4T

Altech spring clamp ground block snaps on the DIN rail, making a reliable electrical connection between the DIN rail and the terminal block.

### CSCFL4T

Altech spring clamp fuse blocks provide protection in electrical circuits. These fuse blocks accept standard Ø5x20 and Ø5x25 mm fuses.

### CTS16U

CTS16U is a standard feed-through terminal block for 12-4 AWG wires.

CSCGT4T



CSCFL4T



CST16U



Terminal Width	6 mm		8 mm		12 mm	
Stripping Length	9 mm		9 mm		18 mm	
Insulation Material	Polyamide 6.6		Polyamide 6.6		Polyamide 6.6	
Type of Connection	2 spring clamps		2 spring clamps & 2 slots for interconnection		2 screw clamps & 1 tapped hole for cross connection	
Ratings						
Wire Range	0.2-4 sq.mm	22-12 AWG	0.2-4 sq.mm	22-12 AWG	6-16 sq.mm	12-4 AWG
Voltage Rating	750 V	600 V	750 V	600 V	750 V	600 V
Current Rating	32 A	-	6.3 A	6.3 A	82 A	85 A
Terminal Block	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
End Plate	EPCSCGT4T	50	EPCSCFL4T	50	EP25U	50
Partition Plate	-	-	-	-	PP25U	50
DIN Rail <i>for ordering information refer to page 58</i>						
End Stop	CA702	50	CA702	50	CA702	50
	CA802	50	CA802	50	CA802	50
Marking Tags (MT Type)	MT6	100	MT8	100	MT12	100
Continuous 90mm strip	MT9F	10	MT9F	10	MT9F	10