



## Overview

Lead time	Usually Ships within 3 Weeks
-----------	------------------------------

## General

Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack mounting support rails Smart UPS signalling RS-232 cable USB cable
Product web sub-family	TAA Compliant
Performance multiplier	1
Number of tare power	98 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	S
Value multiplier	1

## Physical

Cable length	2.44 m
Number of rack unit	2U
Colour	Black
Depth	68.3 cm
Height	8.6 cm
Mounting location	Front
Mounting preference	Lower
Net weight	44.28 kg
Mounting mode	Rack-mounted

Two post mountable	0
USB compatible	Yes
Width	48 cm

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA L5-30P
Input voltage limits	75...154 V adjustable 82...144 V
Number of cables	1
Input voltage	120 V

## Output

Rated power in W	2700 W
Maximum configurable power in W	2700 W
Harmonic distortion	Less than 5 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	6 NEMA 5-15R 2 NEMA 5-20R
Curve equation	Efficiency
Curve fixed loss	0.0044
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0
Curve square loss	0.0201
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 120V/60Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	120 V
Maximum configurable power in VA	2880 VA
Rated power in VA	2880 VA
Transfer time	4 ms typical : 8 ms maximum

## Conformance

Product certifications	CSA TAA compliance
Standards	FCC part 15 class A UL 1778
Equipment protection policy	Lifetime : \$150000

## Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	348 Btu/h
Show note OP temperature	No

### Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Liquid value	0
Battery curve	C
Battery charger power	188 W rated
Battery power in VAH	566 VAh runtime
Battery life	3...5 year(s)
Extended runtime	0

### Communications & Management

Free slots	1
Control panel	LED status display with on line : on battery : replace battery and overload indicators Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm


### Surge Protection and Filtering

Surge energy rate	459 J
-------------------	-------

### Packing Units

Package 1 Weight	51.7 kg
Package 1 Height	25.4 cm
Package 1 width	60 cm
Package 1 Length	98 cm
Number of Units in Package 3	8

### Offer Sustainability

Sustainable offer status	Green Premium product
Energy Star	<a href="#">ENERGY STAR UPS V1.0 (USA)</a> 
RECh Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product

### Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---