




Part Number	Count	Width, Nominal	
111-2413-009	9	.396	(10,06mm)
111-2413-010	10	.44	(13,41mm)
111-2413-012	12	.528	(11,18mm)
111-2413-015	15	.66	(16,76mm)
111-2413-020	20	.88	(22,35mm)
111-2413-030	30	1.32	(33,53mm)

PHYSICAL

Conductors: 24 AWG 7/32 Tinned Copper
 Insulation: .010" Nom. PVC
 Color Code: Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White, Black and Repeat
 Temp. Rating: 105°C

ELECTRICAL

Voltage Rating: 300 V
 Current Rating: 2.2 A @ 10°C Rise Above Ambient
 Insulation Res.: 10^{10} ohms - 10 ft Min.
 Cable Style: UL AWM Style 2693 (105°C, 300V)

DRAWN	PROD ENG	QA	MKT	ECN #	DRAWING NO.	AMPHENOL SPECTRA-STRIP 720 SHERMAN AVE TEL (203) 281-3200 HAMDEN CT 06514 FAX (203) 281-5872	Rev C
FITS 7/31/03	6/16/11			7387	TITLE: Spectra-Bond® Parallel		SHEET 1 of 1
					Conductor Cable		