


# Modular FLATPAQ

Modular Board-To-Board  
Hot Plug High Current Power Connectors

Modular FLATPAQ™ connectors provide custom solutions to hot pluggable AC and DC power needs in a board-to-board format. By using off-the-shelf modular components, power and signal

modules, guide pins and other available features can be combined in a configuration to meet your exact needs. Simply define which modules are required and in what sequence,

using the Layout Sheet provided, and Elcon will provide samples, typically within one week.



## FEATURES

- Custom configurable modular design
- 35A hot pluggable contacts
- Blind-mating
- Sequenced mating for power & signal
- Solder or press-fit terminations
- Active guide pin
- Low insertion force
- Off-the-shelf modular components

## APPLICATIONS

- Board-to-board power connections
- Power supplies, UPS
- Telecommunications
- Computers and file servers
- Aerospace power applications

### High Current Capabilities

FLATPAQ uses Elcon's highly reliable CROWN BAND technology that guarantees low insertion and extraction forces, minimal voltage drop and reduced temperature rise. UL rated at 35A, FLATPAQ may handle even higher currents when mounted on boards with 5 oz. copper traces or onto a busbar (see Test Data on back cover).



### Guide Pins

FLATPAQ guide modules, both passive and active (for premate ground), are offered to provide increased gatherability for aligning connectors during blind mating.

### Contact Termination Options

FLATPAQ offers a variety of contact terminations for mounting to printed circuit boards, such as compliant press-fit, solder tail length options, and a retentive feature that holds the connector in place prior to soldering.

### Sequenced Mating

Power blades are available in standard, postmate and premate lengths, allowing mating sequences suited to any design requirement. Signal contacts are available in standard and premate lengths.<sup>(1)</sup>

### Regulatory Agency Evaluations


Modular FLATPAQ has been evaluated by Underwriters Laboratories Inc. to the U.S. standard UL1997 (USR); by UL (CNR) and CSA to the Canadian standard C22.2 No. 182.3-M1987 for use in data, signal, control and power applications; and by TÜV to the European standard EN60950.<sup>(2)</sup>



#### Notes:

<sup>(1)</sup> Consult Elcon for details.

<sup>(2)</sup> If the equipment where the Elcon connector is used requires other end product certification, please contact the pertinent regulatory agency.



# FLATPAQ Connector Layout

Use this sheet to specify the desired connector layout. Please copy this sheet prior to completion to allow reuse.

## INSTRUCTIONS

- 1 Indicate the connector layout by filling in the FP number of each module required in the boxes below, one per box. Use one form per mated pair.
- 2 The left to right order of the modules should match the **mating face views** of the connector. **When laying out right angle assemblies**, make sure that you look at the mating face with the termination tails facing downwards.
- 3 For solder terminated assemblies, indicate the tail length for each half of the connector and whether the retentive feature is required using the checkboxes to the right of the layout grid.

Upon receipt of this form, Elcon will generate a Customer Use Drawing for you to check and approve prior to connector production.

Write the "FP" numbers to indicate the layout of one half of the connector assembly, matching the left to right order with the mating face view of the connector (right angle assembly tails facing downwards).

FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	<b>Solder tail options</b>	
														<input type="checkbox"/> .062" thick board	<input type="checkbox"/> .125" thick board
														<input type="checkbox"/> .093" thick board	<input type="checkbox"/> Retentive feature


Write the "FP" numbers to indicate the layout of the mate to the above assembly, matching the left to right order with the mating face view of the connector (right angle assembly tails facing downwards).

FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	FP	<b>Solder tail options</b>	
														<input type="checkbox"/> .062" thick board	<input type="checkbox"/> .125" thick board
														<input type="checkbox"/> .093" thick board	<input type="checkbox"/> Retentive feature


## SOLDER TERMINATED MODULES

### STRAIGHT TAILS


#### 250V Power Modules




FP100  
Socket



FP101  
Standard



FP102  
Premate



FP103  
Postmate

#### 600V Power Modules



FP116  
Socket



FP117  
Standard




FP118  
Premate




FP119  
Postmate

#### Signal Modules



FP300  
24-pin



FP301  
24-pin socket



FP312  
6-pin



FP313  
6-pin socket

### RIGHT ANGLE TAILS

#### 250V Power Modules



FP104  
Socket



FP105  
Standard



FP106  
Premate



FP107  
Postmate

#### 600V Power Modules



FP120  
Socket



FP121  
Standard




FP122  
Premate




FP123  
Postmate

#### Signal Modules



FP302  
24-pin



FP303  
24-pin socket



FP314  
6-pin



FP315  
6-pin socket

### SOLDER TAIL OPTIONS

The following options are available when specifying solder terminated assemblies. Indicate these options by marking the checkboxes to the right of the connector layout grid.


#### ■ Tail length

Solder tails are available in 3 lengths. Select depending on board thickness and mounting style (straight or right angle assembly). See table below or, for more details, refer to TERMINATION OPTIONS at the bottom of next page.

Board Thickness	Straight Tails	Right Angle Tails
.062"	.115" (2.9 mm) Nominal	.115" (2.9 mm) Nominal
.093"	.143" (3.6 mm) Nominal	.177" (4.5 mm) Nominal
.125"	.177" (4.5 mm) Nominal	.177" (4.5 mm) Nominal


#### ■ Retentive feature

Consists of precisely formed solder tails on the contacts of the outermost power modules of the assembly, as shown in the drawing below.




## PRESS-FIT TERMINATED MODULES For 0.093" or thicker boards


#### 250V Power Modules




FP200  
Socket



FP201  
Standard




FP202  
Premate




FP203  
Postmate


#### 600V Power Modules




FP216  
Socket



FP217  
Standard



FP218  
Premate




FP219  
Postmate

#### Signal Modules




FP412  
6-pin



FP400  
24-pin



FP413  
6-pin socket




FP401  
24-pin socket

## OTHER MODULES

#### Mounts



FP500  
Left flange  
mount



FP501  
Right flange  
mount


#### Guides




FP502  
Straight passive  
guide socket



Right angle  
guide sockets  
FP506 Passive  
FP516 Active



Straight guide pins  
FP503 Passive  
FP515 Active, M3  
FP517 Active, 4-40



FP507  
Right angle  
passive  
guide pin

#### Spacers (without contacts)



FP511  
Straight  
250V spacer



FP512  
Right angle  
250V spacer



FP513  
Straight  
600V spacer



FP514  
Right angle  
600V spacer


## DIMENSIONS

The drawings below show module dimensions for one of the countless layouts possible with Modular FLATPAQ. These drawings are for reference only; actual engineering design work should be based on the Customer User Drawing supplied by Elcon for your particular module configuration.


### Power Blade Length

Blade Type	Dimension "A"	
	Inches	mm
Premate	.492	12.50
Standard	.413	10.50
Postmate	.335	8.50

### Straight Assembly




### PC Board Footprint



## TERMINATION OPTIONS

### Solder termination

Solder termination is available in three lengths for straight connectors, and in two lengths for right-angle assemblies. Please refer to the table below for board thicknesses and recommended tail lengths.




### Compliant press-fit termination

Compliant press-fit termination is available for straight assemblies only, and it is designed for use with boards 0.093" thick and above.

### Tooling for compliant press-fit assemblies

Press plates are recommended for compliant press-fit assemblies. Elcon will provide details of the recommended tooling fixture for each assembly.



### Relationship between tail length and board thicknesses

Board Thickness	Dimension "A"	
	Straight Mounting	Right Angle Mounting
.062"	.100" - .140" (2.55 - 3.57 mm) [.115" (2.92mm) nominal]	.100" - .140" (2.55 - 3.57 mm) [.115" (2.92mm) nominal]
.093"	.130" - .170" (3.30 - 4.32 mm) [.143" (3.6 mm) nominal]	.160" - .200" (4.06 - 5.08 mm) [.177" (4.5 mm) nominal]
.125"	.160" - .200" (4.06 - 5.08 mm) [.177" (4.5 mm) nominal]	.160" - .200" (4.06 - 5.08 mm) [.177" (4.5 mm) nominal]

### Insertion & extraction forces of compliant modules

Forces:	Tested per MIL-C-28859 (reference only)
Push In:	11.2 - 22.5 lbs. per pin (50 - 100N)
Push Out:	10.1 - 20.2 lbs. per pin (45 - 90N)



# Product Specifications


MATERIALS			
Insulators			PPA, UL 94-V-0 flammability rated, color black
Signal Contacts			Solder termination brass alloy per ASTM-B-36; compliant termination phosphor bronze alloy per ASTM-B-103, selectively plated with gold per MIL-G-45204, Type II, Grade C, Class 0 (30μin minimum) and bright tin/lead per MIL-T-10727, Type 1 (100μin minimum) on terminations, all over nickel per QQ-N-290, Class 2 (50μin minimum)
Crown Bands			Beryllium copper alloy per ASTM-B-194, selectively plated with gold per MIL-G-45204, Type II, Grade C, Class 0 (30μin minimum), over nickel per QQ-N-290, Class 2 (50μin minimum)
Power Socket Contacts			Phospor bronze alloy per ASTM-B-103, selectively plated with bright tin/lead per MIL-T-10727, Type 1 (100μin minimum) on terminations, over nickel per QQ-N-290
Power Blade Contacts			Copper alloy per ASTM-B-152, selectively plated with gold per MIL-G-45204, Type II, Grade C, Class 0 (30μin minimum), over nickel per QQ-N-290, Class 2 (50μin minimum)
Other Modules	Passive Guide Pin		Brass alloy per ASTM-16 plated with nickel per AMS2404
	Activated Guide Pin		Tellurium copper alloy per ASTM-B-301, plated with silver per QQ-S-365
	Activated Guide Socket Contact		Phosphor bronze per ASTM-B-103, selectively plated
ELECTRICAL			
Regulatory Agency Ratings	Power Contact	UL (USR)/TÜV	35A at 250V (50 cycles, hot plug module)
		UL (CNR)/CSA	20A at 250V (50 cycles, hot plug module)
	Signal Contact	UL (USR)/TÜV	3A
		UL (CNR)/CSA	2.5A
Contact Resistance	Power Contact		2mΩ maximum initial, (3mΩ maximum after 500 cycles durability), at 35A per MIL-STD 1344, Method 3004
	Signal Contact		15mΩ maximum initial, (30mΩ maximum after 500 cycles durability), at 100mA, 20mV, per MIL-STD 1344, Method 3002
Insulation Resistance	Power Contact		5,000MΩ minimum at 500VDC for 2 minutes, per MIL-STD 1344 Method 3003
	Signal Contact		
Dielectric Strength	Power Contact		1,500VDC for 1 minute, per MIL-STD 1344, Method 3001
	Signal Contact		
MECHANICAL			
Insertion Force	Power Contact		4.0lbf maximum
	Signal Contact		5.0ozf maximum using .0305" (.775mm) diameter steel test pin
Extraction Force	Power Contact		1.0lbf minimum
	Signal Contact		0.5ozf minimum using .0295" (.749mm) diameter steel test pin
Durability	Power Contact		500 cycles, per MIL-STD-1344, Method 2016
	Signal Contact		
Contact Retention	Power Contact		10.0lbf minimum
	Signal Contact		5.0lbf minimum
Tooling			Press fixture is recommended for compliant press fit assemblies Consult Elcon for details.
Marking			Connectors are marked with manufacturer's logo, part number and lot code.
ENVIRONMENTAL			
Temperature Rating			-40°C to +105°C
Vibration			MIL-STD 1344, Method 2005, Test Condition II
Shock			MIL-STD 1344, Method 2004, Test Condition I
Humidity			MIL-STD 1344, Method 1002, Type 1, Test Condition B
Temperature Life			MIL-STD 1344, Method 1005, Test Condition 4D (105 ±2°C, 1,000 hours)
Solderability			MIL-STD 202, Method 208




# Test Data

The two graphs below show the performance of Modular FLATPAQ in terms of temperature rise and voltage drop against current. Both tests were performed on 250V power modules mounted on PC boards with 2 oz., 3 oz. and 5 oz. copper traces.

## ■ TEMPERATURE RISE



## ■ VOLTAGE DROP



## Dedicated FLATPAQ

Popular configurations are available as premolded FLATPAQ connectors. Elcon will automatically suggest the optimum solution for your application from all currently tooled insulators. For more information, request Dedicated FLATPAQ product literature from Elcon.



### SERVERPAK

Cost-effective FLATPAQ specifically designed for high-end PC servers. SERVERPAK features 8 power and 24 signal contacts in less than 3.5" (90 mm) of length.



### Dedicated FLATPAQ

This is one of the many dedicated FLATPAQ connectors that replicate the modular FLATPAQ, resulting in a more cost effective solution.



Visit us on the web at [www.elcon-products.com](http://www.elcon-products.com)

You can find the latest version of this brochure on our website.



Elcon Products International Co.  
PO Box 1885  
Fremont, CA 94538  
Tel: (510) 490-4200  
Fax: (510) 490-3740  
[sales@elcon-products.com](mailto:sales@elcon-products.com)

Elcon Products International Co.  
7 Merlin Court, Gatehouse Close  
Aylesbury, Bucks HP19 3DP England  
Tel: 44-1296-331855  
Fax: 44-1296-331856  
[sales-uk@elcon-products.com](mailto:sales-uk@elcon-products.com)

Nihon Elcon KK  
5F Bonita Shinnakano Bldg.  
4-1-3-Chuo, Nakano-ku  
Tokyo 164 Japan  
Tel: 81-3-5385-7781  
Fax: 81-3-5385-7786  
[sales-jp@elcon-products.com](mailto:sales-jp@elcon-products.com)

Elcon Products International Co.  
Parque Empresarial de S. Fernando de Henares  
Edificio Italia, Planta Baja  
28830 San Fernando de Henares  
Madrid, Spain  
Tel: 34-91-655-5007  
Fax: 34-91-655-7607  
[sales-sp@elcon-products.com](mailto:sales-sp@elcon-products.com)