



U.S. [Visit Amprobe Europe]

[Home](#) [Products](#) [Where to Buy](#) [Promotions](#) [Videos & Training](#) [Service & Support](#) [News & Events](#)[Home](#) | [Products](#) | [Environmental Test](#) | [Light](#) | [Contact us](#) [Refer this page](#)

LT-10 Lamp Tester



Be the first to write a review

Before you buy, download rebate form for a FREE GIFT.
[Download Form](#)[Overview](#) [Reviews](#) [Features](#) [Specifications](#) [Models and Accessories](#) [Resources](#)

Specifications	
Compatible lamps	T2, T4, T5, T8, T9, T10, T12 and fluorescent energy saving light bulbs
Test voltage	Approximately 3 kV / 280 kHz
Field strength	Approximately 100 μ V/m at 260 – 300 kHz
Maximum antenna length	48"
Filament test	T2, T4, T5, T8, T9, T10, T12
VolTect™ non-contact voltage detection	AC 90 V to AC 600 V, 50/60 Hz CAT II 300 V, CAT I 600 V
Supplied with	48" antenna, adaptor plate, users manual, battery and carrying case

Specifications	Range
Compatible lamps	T2, T4, T5, T8, T9, T10, T12 and fluorescent energy saving light bulbs
Test voltage	Approximately 3 kV / 280 kHz
Field strength	Approximately 100 μ V/m at 260 – 300 kHz
Maximum antenna length	48"
Filament test	T2, T4, T5, T8, T9, T10, T12
VolTect™ non-contact voltage detection	AC 90 V to AC 600 V, 50/60 Hz CAT II 300 V, CAT I 600 V
Non-contact voltage sensitivity with probe tip (typical)	LED illuminates and beeps at approx. 3 mm (0.12 in) distance from a wire carrying 120 Vac LED illuminates and beeps at approx. 5 mm (0.2 in) distance from a wire carrying 230 Vac
Drop proof	36"
Operating time	One second ON, one second OFF for maximum five cycles and wait for 1 minute before taking another measurement
Operating temperature	–10°C to +50°C (14°F to 122°F) \leq 85% RH
Storage temperature	–10°C to +50°C (14°F to 122°F) \leq 85% RH
Operating altitude	Up to 2000 meters
Battery	One 9V lithium or alkaline battery only, 6LR61/6LF22/MN1604 or equivalent.
Battery life	Up to 500 tests (Alkaline typically)

Search

Find Resources

 Select

Find Products

 Select

Related Products



2 reviews

[Amprobe AM-530 True-rms Electrical Contractor Multimeter »](#)

1 review

[Amprobe LM-100 Light Meter »](#)

1 review

[Amprobe LM-200 LED Light Meter »](#)

Dimensions (L x W x H)	Approximately 170 x 40 x 24 mm (6.69 x 1.57 x 0.94 in) without antenna
Weight	Approximately 80 g (0.18 lb) with battery installed, excluding 48" antenna
Safety compliance	IEC 61010-1, UL 61010-1, CAN/CSA-C22.2 No. 61010-1-04
EMC compliance	IEC 61326-1
Certification	CSA and CE
Calibration	NA
Warranty	1 Year

Follow us 

[Home](#) | [About Us](#) | [Privacy Statement](#) | [Site Map](#) | [Contact Us](#)

© 1995 – 2013 Amprobe
