

### FEATURES

**Low input offset voltage:** 150  $\mu\text{V}$  maximum  
**Low offset voltage drift over  $-55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ :** 1.2  $\text{pV}/^{\circ}\text{C}$  maximum  
**Low supply current (per amplifier):** 725  $\mu\text{A}$  maximum  
**High open-loop gain:** 5000  $\text{V}/\text{mV}$  minimum  
**Input bias current:** 3 nA maximum  
**Low noise voltage density:** 11  $\text{nV}/\sqrt{\text{Hz}}$  at 1 kHz  
**Stable with large capacitive loads:** 10 nF typical  
**Pin-compatible to LM148, HA4741, RM4156, and LT1014,**  
**with improved performance**  
**Available in die form**

### GENERAL DESCRIPTION

The OP400 is the first monolithic quad operational amplifier that features OP77-type performance. Precision performance is not sacrificed with the OP400 to obtain the space and cost savings offered by quad amplifiers.

The OP400 features an extremely low input offset voltage of less than 150  $\mu\text{V}$  with a drift of less than 1.2  $\mu\text{V}/^{\circ}\text{C}$ , guaranteed over the full military temperature range. Open-loop gain of the OP400 is more than 5 million into a 10 k $\Omega$  load, input bias current is less than 3 nA, CMR is more than 120 dB, and PSRR is less than 1.8  $\mu\text{V}/\text{V}$ . On-chip Zener zap trimming is used to achieve the low input offset voltage of the OP400 and eliminates the need for offset nulling. The OP400 conforms to the industry-standard quad pinout, which does not have null terminals.

### FUNCTIONAL BLOCK DIAGRAMS




Figure 1. 14-Pin Ceramic DIP (Y-Suffix)  
and 14-Pin Plastic DIP (P-Suffix)

Figure 2. 16-Pin SOIC (S-Suffix)

The OP400 features low power consumption, drawing less than 725  $\mu\text{A}$  per amplifier. The total current drawn by this quad amplifier is less than that of a single OP07, yet the OP400 offers significant improvements over this industry-standard op amp. Voltage noise density of the OP400 is a low 11  $\text{nV}/\sqrt{\text{Hz}}$  at 10 Hz, half that of most competitive devices.

The OP400 is pin-compatible with the LM148, HA4741, RM4156, and LT1014 operational amplifiers and can be used to upgrade systems having these devices. The OP400 is an ideal choice for applications requiring multiple precision operational amplifiers and where low power consumption is critical.




Figure 3. Simplified Schematic (One of Four Amplifiers Is Shown)

# SPECIFICATIONS

## ELECTRICAL CHARACTERISTICS

@  $V_S = \pm 15\text{ V}$ ,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.

Table 1.

| Parameter                                | Symbol             | Conditions                                          | OP400A/E |            |     | OP400F   |            |     | OP400G/H |            |     | Unit                    |
|------------------------------------------|--------------------|-----------------------------------------------------|----------|------------|-----|----------|------------|-----|----------|------------|-----|-------------------------|
|                                          |                    |                                                     | Min      | Typ        | Max | Min      | Typ        | Max | Min      | Typ        | Max |                         |
| INPUT CHARACTERISTICS                    |                    |                                                     |          |            |     |          |            |     |          |            |     |                         |
| Input Offset Voltage                     | $V_{OS}$           |                                                     |          | 40         | 150 |          | 60         | 230 |          | 80         | 300 | $\mu\text{V}$           |
| Long-Term Input Voltage Stability        |                    |                                                     |          | 0.1        |     |          | 0.1        |     |          | 0.1        |     | $\mu\text{V}/\text{mo}$ |
| Input Offset Current                     | $I_{OS}$           | $V_{CM} = 0\text{ V}$                               |          | 0.1        | 1.0 |          | 0.1        | 2.0 |          | 0.1        | 3.5 | nA                      |
| Input Bias Current                       | $I_B$              | $V_{CM} = 0\text{ V}$                               |          | 0.75       | 3.0 |          | 0.75       | 6.0 |          | 0.75       | 7.0 | nA                      |
| Input Noise Voltage                      | $e_{n\text{ p-p}}$ | 0.1 Hz to 10 Hz                                     |          | 0.5        |     |          | 0.5        |     |          | 0.5        |     | $\mu\text{V p-p}$       |
| Input Resistance Differential Mode       | $R_{IN}$           |                                                     |          | 10         |     |          | 10         |     |          | 10         |     | M $\Omega$              |
| Input Resistance Common Mode             | $R_{INCM}$         |                                                     |          | 200        |     |          | 200        |     |          | 200        |     | G $\Omega$              |
| Large Signal Voltage Gain                | $A_{VO}$           | $V_O = \pm 10\text{ V}$                             |          |            |     |          |            |     |          |            |     |                         |
|                                          |                    | $R_L = 10\text{ k}\Omega$                           | 5000     | 12,000     |     | 3000     | 7000       |     | 3000     | 7000       |     | V/mV                    |
|                                          |                    | $R_L = 2\text{ k}\Omega$                            | 2000     | 3500       |     | 1500     | 3000       |     | 1500     | 3000       |     | V/mV                    |
| Input Voltage Range <sup>1</sup>         | IVR                |                                                     | $\pm 12$ | $\pm 13$   |     | $\pm 12$ | $\pm 13$   |     | $\pm 12$ | $\pm 13$   |     | V                       |
| Common-Mode Rejection                    | CMR                | $V_{CM} = 12\text{ V}$                              | 120      | 140        |     | 115      | 140        |     | 110      | 135        |     | dB                      |
| Input Capacitance                        | $C_{IN}$           |                                                     |          | 3.2        |     |          | 3.2        |     |          | 3.2        |     | pF                      |
| OUTPUT CHARACTERISTICS                   |                    |                                                     |          |            |     |          |            |     |          |            |     |                         |
| Output Voltage Swing                     | $V_O$              | $R_L = 10\text{ k}\Omega$                           | $\pm 12$ | $\pm 12.6$ |     | $\pm 12$ | $\pm 12.6$ |     | $\pm 12$ | $\pm 12.6$ |     | V                       |
| POWER SUPPLY                             |                    |                                                     |          |            |     |          |            |     |          |            |     |                         |
| Power Supply Rejection Ratio             | PSRR               | $V_S = 3\text{ V to } 18\text{ V}$                  |          | 0.1        | 1.8 |          | 0.1        | 3.2 |          | 0.2        | 5.6 | $\mu\text{V}/\text{V}$  |
| Supply Current per Amplifier             | $I_{SY}$           | No load                                             |          | 600        | 725 |          | 600        | 725 |          | 600        | 725 | $\mu\text{A}$           |
| DYNAMIC PERFORMANCE                      |                    |                                                     |          |            |     |          |            |     |          |            |     |                         |
| Slew Rate                                | SR                 |                                                     | 0.1      | 0.15       |     | 0.1      | 0.15       |     | 0.1      | 0.15       |     | V/ $\mu\text{s}$        |
| Gain Bandwidth Product                   | GBWP               | $A_V = 1$                                           |          | 500        |     |          | 500        |     |          | 500        |     | kHz                     |
| Channel Separation                       | CS                 | $V_O = 20\text{ V p-p}$ ,<br>$f_o = 10\text{ Hz}^2$ | 123      | 135        |     | 123      | 135        |     | 123      | 135        |     | dB                      |
| Capacitive Load Stability                |                    | $A_V = 1$ ,<br>no oscillations                      |          | 10         |     |          | 10         |     |          | 10         |     | nF                      |
| NOISE PERFORMANCE                        |                    |                                                     |          |            |     |          |            |     |          |            |     |                         |
| Input Noise Voltage Density <sup>3</sup> | $e_n$              | $f_o = 10\text{ Hz}^3$                              |          | 22         | 36  |          | 22         | 36  |          | 22         |     | nV/ $\sqrt{\text{Hz}}$  |
|                                          |                    | $f_o = 1000\text{ Hz}^3$                            |          | 11         | 18  |          | 11         | 18  |          | 11         |     | nV/ $\sqrt{\text{Hz}}$  |
| Input Noise Current                      | $i_{n\text{ p-p}}$ | 0.1 Hz to 10 Hz                                     |          | 15         |     |          | 15         |     |          | 15         |     | pA p-p                  |
| Input Noise Current Density              | $i_n$              | $f_o = 10\text{ Hz}$                                |          | 0.6        |     |          | 0.6        |     |          | 0.6        |     | pA/ $\sqrt{\text{Hz}}$  |

<sup>1</sup> Guaranteed by CMR test.

<sup>2</sup> Guaranteed but not 100% tested.

<sup>3</sup> Sample tested.

# OP400

@  $V_S = \pm 15\text{ V}$ ,  $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$  for OP400A, unless otherwise noted.

**Table 2.**

| Parameter                          | Symbol     | Conditions                                                                      | Min          | Typ          | Max | Unit                         |
|------------------------------------|------------|---------------------------------------------------------------------------------|--------------|--------------|-----|------------------------------|
| <b>INPUT CHARACTERISTICS</b>       |            |                                                                                 |              |              |     |                              |
| Input Offset Voltage               | $V_{OS}$   |                                                                                 |              | 70           | 270 | $\mu\text{V}$                |
| Average Input Offset Voltage Drift | $TCV_{OS}$ |                                                                                 |              | 0.3          | 1.2 | $\mu\text{V}/^\circ\text{C}$ |
| Input Offset Current               | $I_{OS}$   | $V_{CM} = 0\text{ V}$                                                           |              | 0.1          | 2.5 | nA                           |
| Input Bias Current                 | $I_B$      | $V_{CM} = 0\text{ V}$                                                           |              | 1.3          | 5.0 | nA                           |
| Large Signal Voltage Gain          | $A_{VO}$   | $V_O = \pm 10\text{ V}$ , $R_L = 10\text{ k}\Omega$<br>$R_L = 2\text{ k}\Omega$ | 3000<br>1000 | 9000<br>2300 |     | V/mV                         |
| Input Voltage Range <sup>1</sup>   | IVR        |                                                                                 | $\pm 12$     | $\pm 12.5$   |     | V                            |
| Common-Mode Rejection              | CMR        | $V_{CM} = \pm 12\text{ V}$                                                      |              | 115          | 130 | dB                           |
| <b>OUTPUT CHARACTERISTICS</b>      |            |                                                                                 |              |              |     |                              |
| Output Voltage Swing               | $V_O$      | $R_L = 10\text{ k}\Omega$                                                       | $\pm 12$     | $\pm 12.4$   |     |                              |
| <b>POWER SUPPLY</b>                |            |                                                                                 |              |              |     |                              |
| Power Supply Rejection Ratio       | PSRR       | $V_O = 3\text{ V}$ to $18\text{ V}$                                             |              | 0.2          | 3.2 | $\mu\text{V}/\text{V}$       |
| Supply Current per Amplifier       | $I_{SY}$   | No load                                                                         |              | 600          | 775 | $\mu\text{A}$                |
| <b>DYNAMIC PERFORMANCE</b>         |            |                                                                                 |              |              |     |                              |
| Capacitive Load Stability          |            | $A_V = 1$ , no oscillations                                                     |              | 8            |     | nF                           |

<sup>1</sup> Guaranteed by CMR test.

@  $V_S = \pm 15\text{ V}$ ,  $-25^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$  for OP400E/E,  $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$  for OP400G,  $-40^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$  for OP400H, unless otherwise noted.

**Table 3.**

| Parameter                          | Symbol            | Conditions                                      | OP400E |        |     | OP400F |       |      | OP400G/H |       |      | Unit  |
|------------------------------------|-------------------|-------------------------------------------------|--------|--------|-----|--------|-------|------|----------|-------|------|-------|
|                                    |                   |                                                 | Min    | Typ    | Max | Min    | Typ   | Max  | Min      | Typ   | Max  |       |
| INPUT CHARACTERISTICS              |                   |                                                 |        |        |     |        |       |      |          |       |      |       |
| Input Offset Voltage               | V <sub>OS</sub>   |                                                 |        | 60     | 220 |        | 80    | 350  |          | 110   | 400  | μV    |
| Average Input Offset Voltage Drift | TCV <sub>OS</sub> |                                                 |        | 0.3    | 1.2 |        | 0.3   | 2.0  |          | 0.6   | 2.5  | μV/°C |
| Input Offset Current               | I <sub>OS</sub>   | V <sub>CM</sub> = 0 V<br>E, F, G grades         |        | 0.1    | 2.5 |        | 0.1   | 3.5  |          | 0.2   | 6.0  | nA    |
|                                    |                   | H grade                                         |        |        |     |        |       |      |          | 0.2   | 12.0 | nA    |
| Input Bias Current                 | I <sub>B</sub>    | V <sub>CM</sub> = 0 V<br>E, F, G grades         |        | 0.9    | 5.0 |        | 0.9   | 10.0 |          | 1.0   | 12.0 | nA    |
|                                    |                   | H grade                                         |        |        |     |        |       |      |          | 1.0   | 20.0 | nA    |
| Large-Signal Voltage Gain          | A <sub>VO</sub>   | V <sub>CM</sub> = 0 V<br>R <sub>L</sub> = 10 kΩ | 3000   | 10,000 |     | 2000   | 5000  |      | 2000     | 5000  |      | V/mV  |
|                                    |                   | R <sub>L</sub> = 2 kΩ                           | 1500   | 2700   |     | 1000   | 2000  |      | 1000     | 2000  |      | V/mV  |
| Input Voltage Range <sup>1</sup>   | IVR               |                                                 | ±12    | ±12.5  |     | ±12    | ±12.5 |      | ±12      | ±12.5 |      | V     |
| Common-Mode Rejection              | CMR               | V <sub>CM</sub> = ±12 V                         | 115    | 135    |     | 110    | 135   |      | 105      | 130   |      | dB    |
| OUTPUT CHARACTERISTICS             |                   |                                                 |        |        |     |        |       |      |          |       |      |       |
| Output Voltage Swing               | V <sub>O</sub>    | R <sub>L</sub> = 10 kΩ                          | ±12    | ±12.4  |     | ±12    | ±12.4 |      | ±12      | ±12.6 |      | V     |
|                                    |                   | R <sub>L</sub> = 2 kΩ                           | ±11    | ±12    |     | ±11    | ±12   |      | ±11      | ±12.2 |      | V     |
| POWER SUPPLY                       |                   |                                                 |        |        |     |        |       |      |          |       |      |       |
| Power Supply Rejection Ratio       | PSRR              | V <sub>S</sub> = ±3 V to ±18 V                  |        | 0.15   | 3.2 |        | 0.15  | 5.6  |          | 0.3   | 10.0 | μV/V  |
| Supply Current per Amplifier       | I <sub>SY</sub>   | No load                                         |        | 600    | 775 |        | 600   | 775  |          | 600   | 775  | μA    |
| DYNAMIC PERFORMANCE                |                   |                                                 |        |        |     |        |       |      |          |       |      |       |
| Capacitive Load Stability          |                   | No oscillations                                 |        | 10     |     |        | 10    |      |          | 10    |      | nF    |

<sup>1</sup> Guaranteed by CMR test.

## ABSOLUTE MAXIMUM RATINGS

Table 4.

| Parameter                            | Rating                                          |
|--------------------------------------|-------------------------------------------------|
| Supply Voltage                       | $\pm 20$ V                                      |
| Differential Input Voltage           | $\pm 30$ V                                      |
| Input Voltage                        | Supply voltage                                  |
| Output Short-Circuit Duration        | Continuous                                      |
| Storage Temperature Range            |                                                 |
| P, Y Packages                        | $-65^{\circ}\text{C}$ to $+150^{\circ}\text{C}$ |
| Lead Temperature (Soldering 60 sec)  | $300^{\circ}\text{C}$                           |
| Junction Temperature ( $T_J$ ) Range | $-65^{\circ}\text{C}$ to $+150^{\circ}\text{C}$ |
| Operating Temperature Range          |                                                 |
| OP400A                               | $-55^{\circ}\text{C}$ to $+125^{\circ}\text{C}$ |
| OP400E, OP400F                       | $-25^{\circ}\text{C}$ to $+85^{\circ}\text{C}$  |
| OP400G                               | $0^{\circ}\text{C}$ to $70^{\circ}\text{C}$     |
| OP400H                               | $-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$  |

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Absolute maximum ratings apply to both dice and packaged parts, unless otherwise noted.

## THERMAL RESISTANCE

$\theta_{JA}$  is specified for worst-case mounting conditions, that is,  $\theta_{JA}$  is specified for device in socket for CERDIP and PDIP packages;  $\theta_{JA}$  is specified for device soldered to printed circuit board for SOIC package.


Table 5. Thermal Resistance

| Package Type           | $\theta_{JA}$ | $\theta_{JC}$ | Unit                        |
|------------------------|---------------|---------------|-----------------------------|
| 14-Pin Ceramic DIP (Y) | 94            | 10            | $^{\circ}\text{C}/\text{W}$ |
| 14-Pin Plastic DIP (P) | 76            | 33            | $^{\circ}\text{C}/\text{W}$ |
| 16-Pin SOIC (S)        | 88            | 23            | $^{\circ}\text{C}/\text{W}$ |

## ESD CAUTION



**ESD (electrostatic discharge) sensitive device.** Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.



COMPLIANT TO JEDEC STANDARDS MS-013-AA  
CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS  
(IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR  
REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

032707-B

Figure 37. 16-Lead Standard Small Outline Package [SOIC\_W]  
Wide Body (RW-16)  
[S-Suffix]

Dimensions shown in millimeters and (inches)

## ORDERING GUIDE

| Model                      | Temperature Range | Package Description | Package Option   |
|----------------------------|-------------------|---------------------|------------------|
| OP400AY                    | −55°C to +125°C   | 14-Lead CERDIP      | Y-Suffix (Q-14)  |
| OP400EY                    | −25°C to +85°C    | 14-Lead CERDIP      | Y-Suffix (Q-14)  |
| OP400FY                    | −25°C to +85°C    | 14-Lead CERDIP      | Y-Suffix (Q-14)  |
| OP400GP                    | 0°C to +70°C      | 14-Lead PDIP        | P-Suffix (N-14)  |
| OP400GPZ <sup>1</sup>      | 0°C to +70°C      | 14-Lead PDIP        | P-Suffix (N-14)  |
| OP400HP                    | −40°C to +85°C    | 14-Lead PDIP        | P-Suffix (N-14)  |
| OP400HPZ <sup>1</sup>      | −40°C to +85°C    | 14-Lead PDIP        | P-Suffix (N-14)  |
| OP400GS                    | 0°C to +70°C      | 16-Lead SOIC_W      | S-Suffix (RW-16) |
| OP400GS-REEL               | 0°C to +70°C      | 16-Lead SOIC_W      | S-Suffix (RW-16) |
| OP400GSZ <sup>1</sup>      | 0°C to +70°C      | 16-Lead SOIC_W      | S-Suffix (RW-16) |
| OP400GSZ-REEL <sup>1</sup> | 0°C to +70°C      | 16-Lead SOIC_W      | S-Suffix (RW-16) |
| OP400HS                    | −40°C to +85°C    | 16-Lead SOIC_W      | S-Suffix (RW-16) |
| OP400HS-REEL               | −40°C to +85°C    | 16-Lead SOIC_W      | S-Suffix (RW-16) |
| OP400HSZ <sup>1</sup>      | −40°C to +85°C    | 16-Lead SOIC_W      | S-Suffix (RW-16) |
| OP400HSZ-REEL <sup>1</sup> | −40°C to +85°C    | 16-Lead SOIC_W      | S-Suffix (RW-16) |
| OP400GBC                   |                   | Die                 |                  |

<sup>1</sup> Z = RoHS Compliant Part.

## SMD PARTS AND EQUIVALENTS

| SMD Part Number <sup>1</sup> | Analog Devices Equivalent |
|------------------------------|---------------------------|
| 5962-8777101M3A              | OP400ATCMDA               |
| 5962-8777101MCA              | OP400AYMDA                |

<sup>1</sup> For military processed devices, please refer to the standard microcircuit drawing (SMD) available at the Defense Supply Center Columbus website.