

# WX1010

1-Channel Soldering Station, 200 W  
Product no.: WX1010N



## Benefits

- › High Powered Digital Soldering Stations WX 1
- › Capacitive glass touch screen is chemical and temperature resistant
- › Turn and click wheel with enter key and finger guide is intuitive to use
- › Multi-language menu , ready for automation using RS232 Serial I/O commands
- › Large graphic LCD display can be viewed from all angles
- › Acts as a benchtop controller for the WHP 1000 / WHP 3000 hot plates
- › Acts as a benchtop controller for the Zero Smog 4V / 6V Filtration units
- › Multi-purpose USB port for parameter configuration and DATA LOGGING
- › Compatible with all WX series soldering pencils
- › Compatible with WXMT-MS desoldering tweezers



### Technical Data

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Dimensions L x W x H (mm)              | 170 x 151 x 130                          |
| Dimensions L x W x H (inches)          | 6, 69 x 5, 94 x 5, 12                    |
| Weight (approx.) in kg                 | 3.2                                      |
| Voltage                                | 120 V                                    |
| Power                                  | 200 W                                    |
| Channels                               | 1                                        |
| Temperature range (depends on tool) °C | 100 - 550                                |
| Temperature range (depends on tool) °F | 200 - 999                                |
| Temperature accuracy °C                | ±9                                       |
| Temperature accuracy °F                | ±17                                      |
| Temperature stability °C               | ±2                                       |
| Temperature stability °F               | ±4                                       |
| Equipotential bonding socket           | Via 3,5 mm pawl socket on back of device |
| Display                                | 255 x 128 dots / Backlighting            |
| Air consumption l/min                  | ---                                      |
| Operating pressure in bar/psi          | ---                                      |
| Capacity l/min                         | ---                                      |
| Vacuum                                 | ---                                      |