

1 2 3 4 5 6 7

A B C D E F G H

A B C D E F G H

NOTES:

MATERIAL

1.Insulator Material:PBT+30%G.F.(UL94V-0),Grey  
 2.Contact Material : Brass  
 3.Contact Plating : 1u" Au selective Over Ni

ELECTRICAL

1.Current Rating : 3.0 AMP  
 2.Withstand Voltage : 1000V AC/minute  
 3.Contact Resistance : 20mΩ max  
 4.Insulation Resistance: 1000MΩ min

ENVIRONMENTAL

1.Operation Temperature: -40°C to +105°C  
 2.Packing : Tray  
 3.10P~18P with slot"M" without slot "N"  
 20P-64P with slot "M" and "N"

Ordering Information

AWH xxG-02x2-IDC

No. of Contacts :  
 10,14,16,20,26,  
 30,34,40,50,60,64

Latch Type  
 0 -without latch  
 2 -with short latches  
 3 -with long latches

without Latch      with short Latch      with long Latch

Short Latch      Long Latch

RoHS compliant

Scale	1:1						Date	Name	Customer-No.
TOLERANCE						Drawn	25.01.2006	Alex	
X.X	±0.40								
X.XX	±0.25	④	Correct drawing of short latch	05.05.2010	Dean	Approved	05.05.2010	Hellwig	ASSMANN WSW-No. <b>AWH xxG-02x2-IDC</b>
X.XXX	±0.15	③	Modify dimension from 7.65 to 7.85	03.11.2009	Dean				Drawing-No.
ANGLE	±3°	②	Update	29.06.2009	Dean				ASS 2231 CO
		①	Drawn	25.01.2006	Alex				Replace
DIM	TOL	Id.	Modification	Date	Name				Sheet

1 2 3 4 5 6 7

H

H