

	1	2	3	4	5	6	7																																																																		
A	Male RECOMMENDED PCB LAYOUT Product Specification Material Insulator : Glass-Filled thermoplastic PBT UL94V-0 rated Contact : Brass Shell : Steel Electrical Contact Resistance : 20 milliohms Max at 1 AMP DC. Insulation Resistance : 1000 megohms at 500 VDC Dielectric Withstanding Voltage : 1000 VAC/rms 60Hz for 1 minute Current Rating : 5AMP Voltage Rating : 250 VAC/rms 60Hz ① Solder temp for wave soldering : 220 ± 5°C, 3-5 s Order Code: A-Dx xx A/KG-xx * on request Contact style: F - Female S - Male Version T3 - without locking bolts, UNC No. of Contacts 09 / 15 / 25 / 37 Standard: Quality class III							A																																																																	
B								B																																																																	
C								C																																																																	
D								D																																																																	
E	Dimensions <table><thead><tr><th>Positions</th><th>A</th><th>B</th><th>C</th><th>E</th></tr></thead><tbody><tr><td>9</td><td>30.81</td><td>24.99</td><td>16.92</td><td>11.08</td></tr><tr><td>15</td><td>39.20</td><td>33.30</td><td>25.25</td><td>19.39</td></tr><tr><td>25</td><td>53.05</td><td>47.04</td><td>38.96</td><td>33.24</td></tr><tr><td>37</td><td>69.40</td><td>63.50</td><td>55.42</td><td>49.86</td></tr></tbody></table>							Positions	A	B	C	E	9	30.81	24.99	16.92	11.08	15	39.20	33.30	25.25	19.39	25	53.05	47.04	38.96	33.24	37	69.40	63.50	55.42	49.86	E																																								
Positions	A	B	C	E																																																																					
9	30.81	24.99	16.92	11.08																																																																					
15	39.20	33.30	25.25	19.39																																																																					
25	53.05	47.04	38.96	33.24																																																																					
37	69.40	63.50	55.42	49.86																																																																					
F								F																																																																	
G	9.4mm Footprint RoHS compliant Unit:mm <table><thead><tr><th>Scale</th><th>Free</th><th></th><th></th><th></th><th></th><th></th><th>Customer-No.</th></tr></thead><tbody><tr><td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td></td><td rowspan="9">ASSMANN WSW-No. A-Dx xx A/KG-T1/T3 Drawing-No. ASS 4889 CO rev02 Sheet 1/2</td></tr><tr><td>X.</td><td>±0.38</td><td></td><td></td><td></td><td></td><td>Drawn</td></tr><tr><td>X.X</td><td>±0.25</td><td></td><td></td><td></td><td></td><td>Approved</td></tr><tr><td>X.XX</td><td>±0.13</td><td>②</td><td>Update the dimension</td><td>27.02.2015</td><td>Winnie</td><td></td></tr><tr><td>DIM</td><td>TOL</td><td>①</td><td>Add the soldering temperature</td><td>24.01.2014</td><td>Winnie</td><td></td></tr><tr><td>X.°</td><td>±3°</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.X°</td><td>±1.0°</td><td>③</td><td>Drawn</td><td>15.08.2012</td><td>Lucas</td><td></td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td></td></tr></tbody></table>							Scale	Free						Customer-No.	TOLERANCE							ASSMANN WSW-No. A-Dx xx A/KG-T1/T3 Drawing-No. ASS 4889 CO rev02 Sheet 1/2	X.	±0.38					Drawn	X.X	±0.25					Approved	X.XX	±0.13	②	Update the dimension	27.02.2015	Winnie		DIM	TOL	①	Add the soldering temperature	24.01.2014	Winnie		X.°	±3°						X.X°	±1.0°	③	Drawn	15.08.2012	Lucas		Angle	TOL	Id.	Modification	Date	Name		G
Scale	Free						Customer-No.																																																																		
TOLERANCE							ASSMANN WSW-No. A-Dx xx A/KG-T1/T3 Drawing-No. ASS 4889 CO rev02 Sheet 1/2																																																																		
X.	±0.38					Drawn																																																																			
X.X	±0.25					Approved																																																																			
X.XX	±0.13	②	Update the dimension	27.02.2015	Winnie																																																																				
DIM	TOL	①	Add the soldering temperature	24.01.2014	Winnie																																																																				
X.°	±3°																																																																								
X.X°	±1.0°	③	Drawn	15.08.2012	Lucas																																																																				
Angle	TOL	Id.	Modification	Date	Name																																																																				
H								H																																																																	
	1	2	3	4	5	6	7																																																																		

