



HIRSCHMANN

A BELDEN BRAND

Product information MAK 40 UM grau/grey


Industrial Connecting Solutions: Circular Connectors: Audio/Video Connectors: DIN EN 60 130-09 Connectors (MAS/MAK series): without locking screw: Straight sockets: MAK 40 UM grau/grey
<https://catalog.beldensolutions.com:443/link/57078-24228-256281-256282-24384-24385-24390-34810/en/conf/ui/state>

Name	MAK 40 UM grau/grey
	socket with insulated handle; solder joint
Delivery informations	
Availability	available
Product description	
Type	MAK 40 UM grau/grey
Order No.	931 086-117
Type of contact	female
Description	socket with insulated handle; solder joint
Housing Color	grey
Number of contacts	4
Conductor size	$\leq 0.34 \text{ mm}^2$
Technical data	
LF output "Phone"	EN 60 130-09
Rated current	4 A
Rated voltage	AC/DC 34 V
Cable diameter	5.5 mm
Type of termination	solder
Material	
Contact material (socket)	brass
Contact surface material	tin plated
Contact bearer material	PA 66/UL standard 94V-2
Housing material	PE
Environmental conditions	
Protection class (IEC 60529)	IP 30
Temperature range	-20 °C to +60 °C
Scope of delivery and accessories	
Packaging	industry package, box; individual parts not assembled, sorted

Industrial Connecting Solutions: Circular Connectors: Audio/Video Connectors: DIN EN 60 130-09 Connectors (MAS/MAK series): without locking screw: Straight sockets: MAK 40 UM grau/grey
<https://catalog.beldensolutions.com:443/link/57078-24228-256281-256282-24384-24385-24390-34810/en/conf/uistate>

Picture

Drawing



Belden Deutschland GmbH
Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.