

Data sheet

Digital Storage Oscilloscopes
Models 2530 & 2532



Essential features for the cost conscious user


The Digital Storage Oscilloscope models 2530 & 2532 deliver essential features and reliable performance at a price you can afford. Analog style controls combined with Auto functions make these oscilloscopes easy to use. Advanced triggering, automatic measurements and FFT functions provide you with many options to debug your circuits. Additionally, the instruments come with PC Software that lets you easily capture, save and analyze waveforms and measurement results.

The 2530 & 2532 are ideal oscilloscopes for education and training and are well suited for applications in service and repair.

Model	Bandwidth	Sample rate	Display
2530	25MHz	250MSa/s	Monochrome
2532	40MHz	500MSa/s	Color

- 25 MHz and 40 MHz bandwidth and sample rate up to 500MSa/s Real Time
- Monochrome (2530) or Color (2532) LCD
- One touch automatic setup for ease of use (Auto)
- 4000 point record length for each channel
- Capture, save and analyze waveform data with the included EasyScope Application Software
- Eleven automatic measurements
- FFT standard plus 4 additional math functions
- Extensive Trigger capabilities including Pulse Width and line-selectable Video trigger
- Save/Recall setup and waveform data
- Multiple language interface

- Security loop
Use the built-in cable channel to secure your oscilloscope to your location



Digital Storage Oscilloscopes

Models 2530 & 2532

Specifications		models	
		2530	2532
Performance Characteristics			
Bandwidth	25 MHz	40 MHz	
Real time sample rate	250 MSa/s	500 MSa/s (two channels interleaved)	
Channels	2		
Display	1/4 VGA Monochrome LCD	1/4 VGA Color LCD	
Rise Time	< 14 ns	< 8.8 ns	
Record Length*	4000 points		
Vertical Resolution	8 bits		
Vertical Sensitivity	2 mV - 5 V/div		
DC gain accuracy	± 3.0 %		
Maximum Input Voltage	300 Vrms, CAT II (between signal and reference BNC connector)		
Position Range	2 mV – 100 mV range ± 2 V 200 mV - 5 V range: ± 40 V		
Bandwidth Limit	-	20 MHz	
Time Base range	25 ns/div – 50 s/div	10 ns/div – 50 s/div	
Timebase accuracy	100 ppm		
Input Coupling	AC, DC,GND		
Input Impedance	1 MΩ in parallel with 13 pf		
Vertical and Horizontal Zoom	Vertically or horizontally expand or compress a live or stopped waveform		
I/O interface	USB device port for connection to PC. (Requires included EasyScope Software for use)		
* The instrument displays 2500 points. 4000 points can be retrieved from internal memory with the included EasyScope application. This feature is supported for a time base settings range of 2.5μs/Div-50ms/Div (scan mode is not active)			
Acquisition Modes			
Sample	Display sample data only		
Peak Detect			
Average	Waveform averaged, selectable from 4,16,32,64,128,256		
Scan Mode	For time base settings 0.1 s/div-50 s/div		
Trigger System			
Trigger Types	Edge, Pulse Width, Video*		
Trigger Modes	Auto, Normal, Single		
Trigger Coupling	AC, DC, LF reject, HF reject		
Trigger Source	CH1, CH2, AC line, Ext, Ext/5		
*Support formats PAL/SECAM, NTSC. Triggers on odd or even field, all lines or line number			
Cursors			
Types	Amplitude, Time		
Measurements	ΔV, ΔT, 1/ΔT		

Automatic Waveform Measurement	
Time	Rise time, Fall Time, Cycle Frequency, Period, Positive Pulse Width, Negative Pulse width
Voltage	MAX, MIN, Peak-Peak, Average, Vrms
Frequency	Hardware counter provides frequency readout of trigger source with 6 digit resolution
Waveform Math	
Math function	FFT, add, subtract, multiply, divide
FFT	Windows: Hanning, Hamming, Blackman, Rectangular 1024 sample points
Autoset	
	Single button automatic setup of both channels for vertical, horizontal and trigger systems
Display	
Display Mode	1/4 VGA (5.7") monochrome LCD (320x240) with adjustable contrast and inverse video
Display Types	Point, Vector
Persistence	Off, 1 s, 2 s, 5 s, infinite
Waveform Interpolation	Sin(x)/x, Linear
Format	YT and XY
Power Requirements	
	100-240 VAC, 50 VAmx, 45 Hz to 440 Hz
Environmental	
Temperature	Operating: 0° C to +55° C Nonoperating: -40° C to +70° C
Humidity	Operating: 95 %RH, 40° C Nonoperating: 90 %RH, 65° C
Altitude	Operating to 4000 m
Pollution Degree	Pollution degree 2 for indoor use only.
Electromagnetic compatibility and Safety	
EMC	This oscilloscope is in compliance with council EMC directive 2004/108/EC
Safety	EN61010-1:2001
General	
Dimensions	290 mm x 150 mm x 300 mm
Width x Height x Depth	11.4 in x 5.9 in x 11.8 in
Weight	4.6 kg (10 Lbs)
One Year Warranty	
Accessories	
Supplied: User Manual, 10:1 Probe set (2 pieces), Power cord , USB interface cable, EasyScope Software Installation disk	
Optional: PR 37A 10:1 Probe, PR 32A Demodulator Probe, PR 55 High Voltage Probe	