

THT Labels: PermaSleeve® Wire Marking Sleeves

www.BradyID.com

B-7642 PermaSleeve® 2HX Polyolefin Wire Marking Sleeves:

Double-Sided Printable, 2" Sleeve Width (Continued from previous page)

Part Number	Sleeves Per Roll	Pieces Per Roll	Approx. Wire Gauge	Range of Wire Diameter Inch (mm)		Supplied Diameter Inch (mm)	Recovered Diameter Inch (mm)	Recovered Wall Thickness Inch (mm)	Sleeve Width Inch (mm)	Rec. Printer	Rec. Ribbon
2HX-250-2-WT-J	7,500	7,500	12 to 8	0.125 (3.2)	0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-250-2-WT-J-*	7,500	--	12 to 8	0.125 (3.2)	0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-250-2-YL-J	7,500	7,500	12 to 8	0.125 (3.2)	0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-250-2-YL-J-*	7,500	--	12 to 8	0.125 (3.2)	0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-375-2-WT	1,000	1,000	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-375-2-WT-*	1,000	--	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-375-2-S	1,000	1,000	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-375-2-S-*	1,000	--	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-375-2-WT-S	250	250	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-375-2-YL-S	250	250	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-375-2-WT-J	2,500	2,500	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-375-2-WT-J-*	1,000	--	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-375-2-YL-J	2,500	2,500	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-375-2-YL-J-*	2,500	--	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-500-2-WT	500	500	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-500-2-WT-*	500	--	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-500-2-S	500	500	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-500-2-S-*	500	--	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-500-2-WT-S	250	250	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-500-2-YL-S	250	250	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-500-2-WT-J	2,500	2,500	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-500-2-WT-J-*	2,500	--	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-500-2-YL-J	2,500	2,500	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-500-2-YL-J-*	2,500	--	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	0.025 (0.6) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-750-2-WT	250	250	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-750-2-WT-2	250	--	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-750-2-S	250	250	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-750-2-S-*	250	--	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-750-2-WT-S	100	100	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-750-2-YL-S	100	100	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-750-2-WT-J	2,500	2,500	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-750-2-WT-J-*	2,500	--	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-750-2-YL-J	2,500	2,500	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2HX-750-2-YL-J-*	2,500	--	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.374 (9.5)	0.030 (0.8) ± 0.003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2HX-1000-2-WT	250	250	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	2.000 (50.8)	PR Plus Printer	R4300/ R6602
2HX-1000-2-WT-*	250	--	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	--	PR Plus Printer	R4300/ R6602
2HX-1000-2-S	250	250	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	2.000 (50.8)	PR Plus Printer	R4300/ R6602
2HX-1000-2-S-*	250	--	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	--	PR Plus Printer	R4300/ R6602
2HX-1000-2-WT-S	100	100	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	2.000 (50.8)	PR Plus Printer	R4300/ R6602
2HX-1000-2-YL-S	100	100	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	0.035 (0.9) ± 0.005 (0.1)	2.000 (50.8)	PR Plus Printer	R4300/ R6602

B-7642 PermaSleeve® HX Polyolefin Single-Sided 2" Width Wire Marking Sleeves continue on next page.

*Choosing Your PermaSleeve Color

You may also choose to order your PermaSleeve HX 2" wire marking sleeves in the colors listed below. Replace the singular asterisk (*) with the abbreviation of the desired color.

Example: HX-094-2-*.4 becomes HX-094-2-**RD**-4

Available Stock Colors:

BK = Black
BL = Blue
BR = Brown
GR = Green
GY = Gray
OR = Orange
RD = Red
VT = Violet
YL = Yellow
WT = White

** Choosing Your PermaSleeve Pieces (optional):

While 1 marker per sleeve is standard, you may also choose to have each sleeve slit multiple times to produce multiple pieces. Replace the double asterisks (**) in the part number to fill in your desired pieces per marker.

Example: HX-187-2-WT-** becomes HX-187-2-WT-4











This "4" means that this 2.000" sleeve is slit into four 0.500" pieces.

Standard Option:

1 marker per sleeve

Other Available Slit Options:

2, 3 or 4 markers per sleeve



See all benchtop printer ribbon parts on page 152 and full material descriptions on pages 164-170.

Approx. wire gauge based on AWG for THHN wire.