

Electronics



Chemask® W - Water Soluble

The water soluble temporary solder masking agent

- Dissolves in water cleaning cycles
- Noncorrosive; safe for sensitive gold, silver and copper
- RoHS Compliant

Applications:

- Rinses off with water cleaning systems
- Can be used as a water soluble tacking compound

CW8 8 fl oz / 236 ml liquid squeeze bottle



CHEMTRONICS[®]

Technical Data Sheet

TDS # CW8

Chemask[®] W

PRODUCT DESCRIPTION

Chemask[®] W solder mask is water soluble and designed to be removed with most aqueous cleaning systems. Chemask[®] W contains high temperature compounds that protect component-free areas from solder during wave soldering. This water soluble formulation is stable to rosin, organic and inorganic fluxes.


- Protects boards from molten solder to 515°F (268°C)
- Compatible with most flux types
- Leaves no corrosive residue
- Non-contaminating
- UV Detectable

TYPICAL APPLICATIONS

During wave soldering, Chemask[®] W protects:

- Component Free Areas
- Gold Connectors
- Gold Fingers
- Pin Connectors

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

Base Material	Synthetic Resin
Color	Blue
Solvent Stability	Dissolves in water with or without detergent
Flux Compatibility	Aqueous Flux
Temperature Stability	515°F (268°C)
Tack-Free Drying Time (10 mils @ 77°F)	20 min.
Cure Time (10 mils @ 77°F)	1 hr.
Viscosity (@ 77°F) (± 300 cps)	15,000 cps
Viscosity Adjusted With	DI Water
Contains UV Indicator	Yes
Solids Content	~ 40%
Flash Point	Nonflammable
Weight/Gallon	8.8 lbs.
Shelflife	1 year
RoHS/WEEE Status	

COMPATIBILITY

Chemask[®] W is generally compatible with most materials used in printed circuit board fabrication. As with any solder masking agent, compatibility with substrate must be determined on a non-critical area prior to use.

APPLICATION METHOD

Squeeze Bottle/Syringe	Yes
Spatula	Yes
Screening	Yes
Stencil	Yes
Automatic Dispensing	Yes

USAGE INSTRUCTIONS

For industrial use only.

Read MSDS carefully prior to use.

Chemask[®] W solder masking agent is engineered for all electronic manufacturing applications. When applying by hand using squeeze bottle or spatula, insure that all areas of the pre-tinned hole are evenly covered on the side to be soldered. For screening applications, properly clean and prepare screen, then apply masking agent in the same manner as solder paste. Automatic dispensing equipment may also be used as appropriate.

REMOVAL: After allowing the mask to become fully cured, the mask may be washed away with water. For optimum performance, water soluble mask may be removed with agitation, ultrasonic, or industrial washing. Surfactants may be added to increase cleaning efficiency.

AVAILABILITY

CW8 8 oz. Squeeze Bottle
CW1 1 Gal. Liquid

ENVIRONMENTAL IMPACT DATA

ENVIRONMENTAL IMPACT DATA

CFC	0.0%	VOC	5.0%
HCFC	0.0%	HFC	0.0%
Cl. Solv.	0.0%	ODP	0.00

CFC, HCFC, CL. SOLV., VOC, and HFC numbers shown are the content by weight. Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. The ODP of this product is 0.0. It is the sum of the ODP of the substances that may contribute to the depletion of stratospheric ozone, based upon the weight of each substance in the product's formulation.

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS[®] does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Information: 800-TECH-401

Product Identification

CHEMASK W

Product Code: CW1, CW5, CW8, CW1C, CW5C, CW8C

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Product Ingredient Information	CAS#	Wt. % Range
Deionized water	7732-18-5	35.0-40.0
Acrylic polymer	mixture	10.0-30.0
Magnesium aluminum silicate	12174-11-7	5.0-10.0
Glycerin	56-81-5	1.0-5.0
Isopropanol	67-63-0	1.0-5.0
Methanol	67-56-1	1.0-5.0
Titanium dioxide	13463-67-7	0.1-1.0

SECTION 3: HAZARD IDENTIFICATION

Emergency Overview: Viscous, opaque blue liquid with mild odor. This product is not flammable. Liquid will irritate eyes and skin under repeated or prolonged exposure.

Potential Health Effects:

Eyes: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.

Skin: Contact causes skin irritation.

Ingestion: Harmful if swallowed. Irritating to mouth, throat and stomach. May cause vomiting.

Inhalation: Harmful if inhaled. High concentrations of vapors in immediate area can displace oxygen and can cause dizziness, unconsciousness, and even death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

Pre-Existing Medical Conditions Aggravated by Exposure: None known

SECTION 4: FIRST AID MEASURES

Eyes: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.

Skin: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persist. Wash clothing separately before reuse.

Ingestion: If swallowed, induce vomiting immediately as directed by medical personnel. Keep head below knees to minimize chance of aspirating material into the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: None to boiling (TCC) LEL/UEL: Not established (% by volume in air)

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Large Spills: Shut off leak if possible and safe to do so. Wear self-contained breathing apparatus and appropriate personal protective equipment. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches which lead to waterways.(mist)

Small Spills: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal.

SECTION 7: HANDLING AND STORAGE

Avoid prolonged or repeated contact with eyes, skin, and clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor or mist. Do not reuse this container. Store in a cool dry place away from heat, sparks and flame. Keep container closed when not in use. Do not store in direct sunlight. **KEEP OUT OF REACH OF CHILDREN.**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:

CHEMICAL NAME	ACGIH TLV	OSHA PEL	ACGIH STEL
Isopropanol	200 ppm	400 ppm	400 ppm
Methanol	200 ppm	200 ppm	250 ppm
Glycerin	10 mg/m (mist)	NA	NA
Acrylic polymer	NA	NA	NA

Work/Hygienic Practices: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. If vapor concentration exceeds TLV, use NIOSH approved organic vapor cartridge respirator. Wear safety glasses with side shields (or goggles) and rubber or other chemically resistant gloves when handling this material.

NFPA and HMIS Codes:

	NFPA	HMIS
Health	1	1
Flammability	0	0
Reactivity	0	0
Personal Protection	-	B

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Opaque blue
Odor: Mild
Vapor Pressure: 12 mm Hg @ 20C
Vapor Density: <1 (Air=1)
Boiling Point: 200F (93C) (initial)
pH: 5.7-6.3

Solubility in Water: Dispersible
Specific Gravity: 1.00 (Water =1)
Evaporation Rate: >1
(Butyl Alcohol= 1)
Percent Volatile: 5.0% by weight
Melting Point: NA

SECTION 10: STABILITY AND CHEMICAL PROPERTIES

Stability: This product is stable. Conditions to Avoid: Do not spray near open flames, red hot surfaces or other sources of ignition.
Incompatibility: Do not mix with powdered alkali and alkaline earth metals or strong oxidizing agents.
Products of Decomposition: Thermal decomposition may release carbon monoxide, carbon dioxide and incompletely burned hydrocarbons.
Hazardous Polymerization: Will not occur Conditions to Avoid: NA

SECTION 11: TOXICOLOGICAL INFORMATION

<u>Inhalation:</u>			<u>Ingestion:</u>		
Isopropanol	LC50/rats	12,000ppm/8hrs	Isopropanol	LD50/rats	5,800 mg/kg
Methanol	LC50/rats	64,000ppm/4hrs	Methanol	LD50	5,628 mg/kg
<u>Skin:</u>			<u>Eyes:</u>		
Isopropanol	rabbit	MLD	Isopropanol	rabbit	MLD-MOD

Cancer Information: No ingredients listed as human carcinogens by NTP or IARC
Reproductive effects: none Teratogenic effects: none Mutagenic effects: none

SECTION 12: ECOLOGICAL INFORMATION

Environmental Impact Information Avoid runoff into storm sewers and ditches which lead to waterways. Water runoff can cause environmental damage.

REPORTING

US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is: **1-800-424-8802**

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

SECTION 14: TRANSPORTATION INFORMATION

Air: Cleaning Compound Not Regulated
Ground: Cleaning Compound Not Regulated

SECTION 15: REGULATORY INFORMATION

SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

Chemical Name	CAS#	Wt. % Range
Methanol	67-56-1	1.0-5.0

This information should be included on all MSDSs copied and distributed for this material.

TOXIC SUBSTANCES CONTROL ACT (TSCA)

All ingredients of this product are listed on the TSCA Inventory.

WHMIS: Class D2B

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16: OTHER INFORMATION

Normal ventilation for standard manufacturing practices is usually adequate. Local exhaust should be used when large amounts are released.

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.