



Terminals DH2


Solder terminal




Drilling pattern



Aux. actuator DH2 (plastic)




Aux. actuator DH3/4 (metal)




Terminals DH3/4


Solder terminal




PCB terminal, RH-side




PCB terminal RH-side



LH-side



Drilling pattern



Electrical rating and operating life (2)

Electrical rating	Operating life		
	at nominal load	mechanical	Code
5-500 mA 30 V DC	30.000	50.000	2
50 mA-300 mA 5-30 V DC	30.000	50.000	3
5 mA-50 mA 5-30 V DC	30.000	50.000	4

Contact configuration (3)

Contact configuration	Code
S.P.D.T.	C

Terminals (4)

	Code
Solder terminal straight, 1.3 x 3.1	B1
PCB terminal, straight, 0.64 x 3.1	C4
PCB terminal, RH-side, 0.64 x 3.1	C5
PCB terminal, LH-side, 0.64 x 3.1	C6

DH2 only available with straight terminals

Auxiliary actuator options (5)

Model	Max. operating force (cN)	Max. pretravel (mm)	Min. overtravel (mm)	Max. movement differential (mm)	Max. rest position (mm)	Operating point (mm)	Code
Without aux. actuator	90	—	0,1	0,07	6,2	5,6 ± 0,15	AA
With aux. actuator	50	—	0,3	0,6	8,5	6,7 ± 0,5	PA (DH2) LA (DH3/4)