

1	2	3	4	5	6	7	8	
				REV.	ECN NO.	DESCRIPTION	SIGN	DATE
				C1	N/A	INITIAL DRAWING	Liu	2019/08/13

48.5 (Ref)

16.8

Cable OD
4~7mm

Seal Nut

Seal Ring

Clamp Ring

Gasket

Male Pin Connector

22XXX331-01

Pin Number

10 Pin

12 Pin

P/N: 22010331-01

P/N: 22012331-01

Pin Assignments Front View

UNIT:mm

TOLERANCE

.X ±0.25

.XX ±0.15

.XXX ±0.05

ANGLES ±1°

DESCRIPTION

Standard Series Push Lock

Female Plug With Male Pin

SCALE: 1:1

SHEET 1 OF 1

REV C1

SIZE A4

* : Inspection Item

PART NO

22XXX331-01

DWG NO

CUSTOMER

DRAWN BY

Liu

CHECKED BY

Mo

APPROVED BY

Panson

DATE

2019/08/13

DATE

2019/08/13

DATE

2019/08/13

CHOGORI®

Specification:

- 1.Operation Temperature: -45℃~105℃..
- 2.Insulation Resistance:100MΩ at DC500V.
- 3.Contact Resistance:<10mΩ
- 4.Withstand Voltage: 1000V AC
- 5.Operating Current:2A
- 6.Operating Voltage:AC 30V
- 7.Waterproof Rate:IP67 (Mated)
- 8.Seal Nut:Nylon, Black
- 9.Seal Ring:Silicon, Black
- 10.Clamp Ring:Nylon, Black
- 11.Gasket:Silicon, Red
- 12.Male Pin:Copper Alloy, Gold Plated
- 13.Connector:Nylon+GF, Black
- 14.RoHS Compliant.
- 15.Cable Range OD:φ3.5mm~φ6.8mm
- 16.Mating Cap: 806-00062-00