

1

2

3

4




5

6

7

8

47.8 (Ref)




23XXX311-XX

Cable Range OD


01 OD: $\phi 3.5\text{mm} \sim \phi 6.5\text{mm}$

02 OD: $\phi 6.5\text{mm} \sim \phi 9.5\text{mm}$

Pin Number



5 Pin



6 Pin

P/N: 23005311-XX

P/N: 23006311-XX

Pin Assignments Front View

A

UNIT:mm



TOLERANCE

.X ± 0.25
.XX ± 0.15
.XXX ± 0.05
ANGLES $\pm 1^\circ$

DESCRIPTION

Middle Series Screw

Female Plug With Male Pin

SCALE

1:1

SHEET

1 OF 1

REV

C1

SIZE

A4

* : Inspection Item

PART NO

23XXX311-XX

DRAWN BY

Liu

DATE

2019/08/13

DWG NO

Mo

DATE

2019/08/13

CUSTOMER

APPROVED BY

Panson

DATE

2019/08/13

DESCRIPTION

INITIAL DRAWING

SIGN

Liu

DATE

2019/08/13

Seal Nut


Seal Ring

Clamp Ring

Gasket


Male Pin

Connector



Specification:

- 1.Operation Temperature: $-45^\circ\text{C} \sim 105^\circ\text{C}$.
- 2.Insulation Resistance: $100\text{M}\Omega$ at DC500V.
- 3.Contact Resistance: $<10\text{m}\Omega$.
- 4.Withstand Voltage: 1500V AC
- 5.Operating Current:10A
- 6.Operating Voltage: AC 125V
- 7.Waterproof Rate: IP67 (Mated)
- 8.Seal Nut:Nylon, Black
- 9.Seal Ring:Silicon, Black.
- 10.Clamp Ring:Nylon, Black
- 11.Gasket: Silicon, Red
- 12.Male Pin: Copper Alloy, Gold Plated
- 13.Connector: Nylon+GF, Black
- 14.RoHS Compliant.
- 15.Mating Cap: 806-00052-00



CHOGORI®