

ACCESSORIES

ACCESSORIES

Filter Assembly (Whisper XL DC, Muffin XL DC, Whisper, Whisper XL, Muffin, Muffin XL)

Part No. 551590



Consists of:

551463 Filter Frame




551494 Filter Element

551453 Mounting Brackets

Recommended cut-out 5.5" x 5.16"



ABOVE HARDWARE SUPPLIED




Note: Filters reduce airflow; i.e. a MX2A3's airflow would be reduced to about 87 CFM with P/N 551590 on fan's inlet at 115VAC, 60 Hz.

TOLERANCE: $\pm .015$ (0.38) ON ALL LINEAR DIMENSIONS

Filter Guard Assembly (Flight 60)

Part No. 557239

30 PPI* Replacement Filter Element
Part No. 557241 (pack of 5)
Also available with 45 PPI Filter
Part No. 557240
45 PPI Replacement Filter Element
Part No. 557242 (pack of 5)
Retainer and guard UL94V-0 plastic
Filter element (media) polyurethane foam




Note: Filters reduce airflow
* PPI denotes "pores per inch"

Filter Guard Assembly (Flight 80, Sprint DC, Sprite DC, Sprite)

Part No. 554141

30 PPI* Replacement Filter Element
Part No. 554139 (Pack of 5)
Also available with 45 PPI Filter
Part No. 554142
45 PPI Replacement Filter Element
Part No. 554140 (Pack of 5)
Retainer and guard UL94V-0 plastic
Replacement filter element (media)
polyurethane foam




Note: Filters reduce airflow; i.e. a ST12A3's airflow would be reduced to about 25 CFM with P/N 554141 on fan's inlet at 12VDC.

* PPI denotes "pores per inch"

TOLERANCE B

Filter Guard Assembly (Flight 90)
Part No. 557218


30 PPI* Replacement Filter Element
Part No. 557220 (pack of 5)
Also available with 45 PPI Filter
Part No. 557219
45 PPI Replacement Filter Element
Part No. 557221 (pack of 5)
Retainer and guard UL94V-0 plastic
Filter element (media) polyurethane foam



Note: Filters reduce airflow
* PPI denotes "pores per inch"

Filter Guard Assembly (Flight 120, Muffin DC, Whisper XL DC, Muffin XL DC, Whisper, Whisper XL, Muffin, Muffin XL)
Part No. 554148


30 PPI* Replacement Filter Element
Part No. 554146 (Pack of 5)
Also available with 45 PPI Filter
Part No. 554149
45 PPI Replacement Filter Element
Part No. 554147 (Pack of 5)
Retainer and guard UL94V-0 plastic
Replacement filter element (media)
polyurethane foam



Note: Filters reduce airflow; i.e. a MX2A3's airflow would be reduced to about 75 CFM with P/N 554148 on fan's inlet at 115VAC, 60 Hz. P/N 554149 would reduce airflow to about 68 CFM.
*PPI denotes "pores per inch"

Filter Assembly (Whisper, Muffin)
Part No. 477712


Consists of:
476000 Filter Frame
271018 Washable Filter Element
271016 Mounting Clip (2)
Installation Instructions



Materials: 476000 Black polycarbonate plastic
271018 Black polycarbonate frame with crimped
18 x 14 mesh aluminum wire filter media
Note: Filters reduce airflow; i.e. MX2A3's airflow would be reduced into about 82 CFM with P/N 477712 on fan's inlet at 115VAC, 60 Hz (UP).

Grille Kit (Whisper, Muffin)
Part No. 478031

Consists of:
476015 Grille (Spiral)
271016 Mounting Clip (2)
Installation Instructions




Materials: Grille—High Impact Polycarbonate Plastic
Clips—.020 (0.5) Thick Spring Steel, black
phosphate finish


TOLERANCE: ±.015 (0.38) ON ALL LINEAR DIMENSIONS

Metal Grille (Whisper, Muffin)
Part No. 477727

Expanded aluminum mesh - snaps onto fan venturi with use of Part No. 271016 mounting clips. (2 REQ'D)




Screen Guard (Flight 120, Muffin DC, Whisper XL DC, Muffin XL DC, Whisper, Whisper XL, Muffin, Muffin XL)
Part No. 550214




Finger Guard (Flight 60)
Part No. 572621

Steel wire, .062 dia., welded and nickel chrome finish
meets UL, CSA .250/6.35 spacing



TOLERANCE B


Finger Guard (Flight 80, Sprint DC, Sprite DC, Sprite)
Part No. 476143



TOLERANCE B

Finger Guard (Flight 80, Sprint DC, Sprite DC, Sprite)
Part No. 550648

Meets UL, CSA .250/6.35 spacing




Color: Black

TOLERANCE A

Finger Guard (Flight 90)
Part No. 554172


Steel wire, .062 dia., welded and nickel chrome finish
Meets UL, CSA .250/6.35 spacing



TOLERANCE B

Finger Guard (Flight 120, Muffin DC, Whisper XL DC, Muffin XL DC, Muffin AC, Whisper, Whisper XL, Muffin, Muffin XL, Skeleton)
Part No. 551147

Meets UL, CSA .250/6.35 spacing




Color: Black

TOLERANCE A

Finger Guard (Flight 120, Muffin DC, Whisper XL DC, Muffin XL DC, Muffin AC, Whisper, Whisper XL, Muffin, Muffin XL, Skeleton)
Part No. 476042


Steel wire, welded and bright zinc plated



TOLERANCE B

Finger Guard (Flight 120, Muffin DC, Whisper XL DC, Muffin XL DC, Muffin AC, Whisper, Whisper XL, Muffin, Muffin XL, Skeleton)
Part No. 550481

Meets UL, CSA .250/6.35 spacing




Color: Black

TOLERANCE A

Finger Guard (Flight 120, Muffin DC, Whisper XL DC, Muffin XL DC, Muffin AC, Whisper, Whisper XL, Muffin, Muffin XL, Skeleton)
Part No. 552934

Meets UL, CSA .250/6.35 spacing




Material: Center Disc: .03 (0.76) THK. C.R.S.
Wire Rings: .062 (1.57) DIA. STEEL
Supports: .080 (2.03) DIA. STEEL
Finish: Bright Zinc Plate with Chromate Treatment

TOLERANCE B

Finger Guard (Galaxy)
Part No. 557216


Made of steel wire finished in bright zinc
Meets UL, CSA .25 dia. spacing



TOLERANCE B

Finger Guard (Galaxy)
Part No. 550651

Material: RTP 305 glass reinforced polycarbonate or
GE Valox 420 polyester
UL Rating 94V-0




Color: Black

TOLERANCE A

Finger Guard (Patriot DC, Patriot)
Part No. 551199


Steel wire, welded and bright zinc plated.
Meets UL, CSA .250/6.35 spacing



TOLERANCE B

Finger Guard (Major DC, Major)
Part No. 550272


Steel wire, welded and bright zinc plated
Meets UL, CSA .250/6.35 spacing



TOLERANCE B

Finger Guard (Biscuit DC, Biscuit)**Part No. 477626**


.030 (.76) thick type 302 stainless steel. Screws onto outlet of blower with (2) 8-32 machine screws (not supplied)



TOLERANCE A

Finger Guard (Tarzan)**Part No. 476136**


Made of steel wire finished in nickel chrome



TOLERANCE B (see below)

Finger Guard (Caravel)**Part No. 476323**

Made of steel wire finished in bright zinc. Mounts using #8 machine screws in the 4 legs equally spaced on 9.688 (246.1) dia.




Note: Also available meeting UL .250 spacing. Call factory for specifications on P/N 557923

TOLERANCE B (see below)

Mounting Clips (Whisper XL DC, Muffin XL DC, Whisper XL, Muffin XL)
Part No. 550113 *Galaxy*


Fits over mounting boss of above fans



5 in./lb. max torque.

Material: .017 (.43) thick tempered spring steel
Finish: Black phosphate

TOLERANCE B (see below)


Plug & Cord
Part No. 550440

UL File No. E42397
GUIDE ZPPW2 Wiring Harness
CSA File No. LR45371

TOLERANCE A (see below)

Mounting Clips (Major DC, Patriot DC, Whisper, Muffin, Major, Patriot)
Part No. 477663 (Flush)
477670 (Standoff)


Fits over .25/.635 mounting flanges of above fans




5 in./lb. max torque.

Material: .017 (.43) thick tempered spring steel
Finish: Black phosphate

TOLERANCE B (see below)

Plug & Cord
Part No. 571064

TOLERANCE B

Plug & Cord
Part No. 428056

TOLERANCE B

TOLERANCE A: .XX = $\pm .03$ (0.8)
 .XXX = $\pm .010$ (0.25)
TOLERANCE B: .XX = $\pm .05$ (1.3)
 .XXX = $\pm .015$ (0.38)