

► Presentation

- General characteristics
- Dimensions
- Connections
- Applications
- Principles

 Send me PDF files by E-mail

 Print

Safety relay - Emergency stop - KNA3-RS

Selling points of the range

- ✚ **KNA3-XS / KNA3-RS / KZP3-RS**
- ✚ "Emergency stop" and "mobile guard monitoring" functions
- ✚ Control device with one or two channels
- ✚ 3 "N/O" safety contacts with linked contacts-6A / 250 AC
- ✚ 1 "N/C" signalling contact
- ✚ Level 4 according to NF.EN 954-1
- ✚ **KNA3-RS (45 mm)**
- ✚ Integrity check on control devices
- ✚ Separate return loop
- ✚ **KZP3-RS (45 mm)**
- ✚ Four input circuits



Part number characteristics

85 100 436

Function	Emergency stop Mobile guard monitoring
Level of safety	4
Safety contacts	3
Casing	45 mm
Supply voltage	24 V AC DC
Connections	Screw terminals
Weight (g)	310
European "Machinery" Directive 89/392/EEC	✓
French decree 92/765-766-768	✓
European "Usage" Directive 89/655/EEC	✓
French decree 93-40 /93-41	✓
IEC 61496-1	✓
IEC 664-1	✓
En 50081-2	✓
EN 50082-2	✓
EN 60204-1	✓
EN 292-1 and 2	✓
EN 954-1	Category 4
EN 418	✓
EN 1088	✓
UL 508	UL
C22-2N ⁰ 14 M91	(c) UL
GS-ET-20	BG
Product available	stocked item