

CW INDUSTRIES

130 James Way

Southampton, PA 18966

Phone: 215-355-7080 • **Fax:** 215-355-1088**Email:** info@cwind.com • **Website:** <http://www.cwind.com>**4000 Series Momentary Miniature Rocker Switches**

For the user with a spring return application, CW offers the 4000 Series Momentary Mini-Rocker Switches. Available circuitries include SPST, SPDT, DPST, and DPDT. For additional design flexibility the single throw versions are available in normally open or normally closed versions. Available in ratings of 8, 13 and 16 amps.

Circuitry:

Specify GRS-4011B / 4021B for Momentary Normally Open.

Specify GRS-4011C / 4021C for Momentary Normally Closed.

Specify GRS-4012A / 4022A for Momentary.

Panel Opening - 0.508" X 0.756" (12.90mm X 19.20mm).

Temperature:

Specify GRS-Series for continuous use temperature rating of +65° C.

Specify GRSV-Series for continuous use temperature rating of +105° C.

Results 1 - 25 of 25

<u>Item #</u>	<u>Circuitry</u>	<u>Switch Function</u>	<u>Electrical Ratings</u>	<u>Actuator Color</u>	<u>Actuator Legend</u>	<u>Housing Color</u>
GRS-4011B-0000	SPST	OFF-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	None	Black
GRS-4011B-0001	SPST	OFF-(ON)	3 A @ 277 VAC 4 A @ 250 VAC 8 A @ 125 VAC	Black	None	Black
GRS-4011B-0014	SPST	OFF-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	None	Black
GRS-4011B-0015	SPST	OFF-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	None	Black
GRS-4011B-0022	SPST	OFF-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Red	Custom	Black
GRS-4011B-1300	SPST	OFF-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	None	Black
GRS-4011C-0000	SPST	ON-(OFF)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T) 3 A @ 277 VAC	Black	None	Black

GRS-4011C-0001	SPST	ON-(OFF)	4 A @ 250 VAC 8 A @ 125 VAC	Black	None	Black
GRS-4011C-0002	SPST	ON-(OFF)	2 A @ 347 VAC 3 A @ 277 VAC 4 A @ 250 VAC 8 A @ 125 VAC	Black	None	Black
GRS-4011C-0003	SPST	ON-(OFF)	2 A @ 347 VAC 3 A @ 277 VAC 4 A @ 250 VAC 8 A @ 125 VAC	White	None	White
GRS-4012A-0000	SPDT	ON-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	None	Black
GRS-4012A-0001	SPDT	ON-(ON)	3 A @ 277 VAC 4 A @ 250 VAC 8 A @ 125 VAC	Black	None	Black
GRS-4012A-0007	SPDT	ON-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	I/O - Horizontal	Black
GRS-4012A-0010	SPDT	ON-(ON)	3 A @ 277 VAC 4 A @ 250 VAC 8 A @ 125 VAC	Black	I/O - Horizontal	Black
GRS-4021B-0000	DPST	OFF-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	None	Black
GRS-4021B-0001	DPST	OFF-(ON)	3 A @ 277 VAC 4 A @ 250 VAC 8 A @ 125 VAC	Black	None	Black
GRS-4021B-0003	DPST	OFF-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	Bump	Black
GRS-4021C-0000	DPST	ON-(OFF)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	None	Black
GRS-4021C-0001	DPST	ON-(OFF)	3 A @ 277 VAC 4 A @ 250 VAC 8 A @ 125 VAC	Black	None	Black
GRS-4021C-0002	DPST	ON-(OFF)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	None	Black
GRS-4022A-0000	DPDT	ON-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Black	None	Black
GRS-4022A-0001	DPDT	ON-(ON)	3 A @ 277 VAC 4 A @ 250 VAC 8 A @ 125 VAC	Black	None	Black
GRS-4022A-0003	DPDT	ON-(ON)	1/2 HP @ 125-250 VAC 10 A @ 250 VAC 13 A @ 125 VAC 5 A @ 14 V (T)	Red	None	Black

