



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.2
 3. TRAVEL (TOTAL): 2.0 mm
 4. OPERATING FORCE: 50gf Max.
 5. RATING: 12V DC, 100mA (Resistive load)
 6. CONTACT RATING: 80m ohms max.
 7. OPERATING TEMP. -20°C to 80°C
 8. MATERIALS
HOUSING: 4/6 NYLON
ACTUATOR: 6T NYLON
COVER/SPRING: STAINLESS STEEL
CONTACTS: SILVER PLATED PHOSPHOR BRONZE
TERMINALS: SILVER PLATED BRASS
9. PACKAGING: TAPE AND REEL, 1900 PIECES PER REEL.

CONTACT CONFIGURATION
SPST NORMALLY OPEN (N.O.) CONTACTS

REV.	ECN No.	DESCRIPTION	DATE	CHKD
H	15120	REVISED TERMINAL SHAPE	7/28/05	RC
G	12884	ADD PCB CENTER TO CENTER	3/5/03	CB
F	12751	REVISED, ADD NEW DIM	1/23/03	CB
E	12201	ADD NOTE 8	5/31/02	CB

SCALE	DATE	DR	DWG	REV
8:1	8/24/98	MM		H

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

900 BG Q

E-SWITCH®
CONTACT CONFIGURATION
SPST NORMALLY OPEN (N.O.) CONTACTS