

E-Z-MICRO-HOOK TEST LEADS

MICRO-HOOK TO .025" (.635mm) SQUARE SOCKET (Illustration NOT to Scale)

Part Number	22AWG	Lead Length
203XM-6-(color)	6"	15cm
203XM-12-(color)	12"	30cm
203XM-18-(color)	18"	45cm
203XM-24-(color)	24"	60cm
203XM-36-(color)	36"	90cm
203XM-48-(color)	48"	120cm
203XM-60-(color)	60"	150cm
203XMC-(color)	48" Coil Cord	



MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See Basic P/N AXM.
.025" (.635mm) SQ. SOCKET: Brass Body. Gold-Plated BeCu Springs. Heat Shrink Insulation.
 Crimp assembly. See P/N 9205.

MICRO-HOOK TO MICRO-HOOK JUMPER (Illustration NOT to Scale)

Part Number	22AWG	Lead Length
204XM-3-(color)	3"	8cm
204XM-6-(color)	6"	15cm
204XM-12-(color)	12"	30cm
204XM-18-(color)	18"	45cm
204XM-24-(color)	24"	60cm
204XM-36-(color)	36"	90cm
204XM-48-(color)	48"	120cm
204XM-60-(color)	60"	150cm
204XMC-(color)	48" Coil Cord	



TEFLON LEAD

Part Number	24AWG	Lead Length
304XM-3-(color)	3"	8cm
304XM-6-(color)	6"	15cm
304XM-12-(color)	12"	30cm
304XM-18-(color)	18"	45cm
304XM-24-(color)	24"	60cm
304XM-36-(color)	36"	90cm
304XM-48-(color)	48"	120cm
304XM-60-(color)	60"	150cm

MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See Basic P/N AXM.

MICRO-HOOK .080" (2.03mm) METER PIN PLUG (Illustration NOT to Scale)


Standard Unit Part Number	22AWG	Lead Length
206XM-(color)	36"	90cm
Additional Lengths		
206XM-12-(color)	12"	30cm
206XM-18-(color)	18"	45cm
206XM-24-(color)	24"	60cm
206XM-48-(color)	48"	120cm
206XM-60-(color)	60"	150cm
206XMC-(color)	48" Coil Cord	



MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See Basic P/N AXM.
.080" METER PIN PLUG: Nickel-Plated Brass Body. Plastic Handle. Solder Assembly. Red, Black. Red will be supplied with colors other than Black unit. See P/N 9207.

MICRO-HOOK TO .250" (6.35mm) INSULATED SPADE LUG (Illustration NOT to Scale)


Standard Unit Part Number	22AWG	Lead Length
208XM-(color)	36"	90cm
Additional Lengths		
208XM-12-(color)	12"	30cm
208XM-18-(color)	18"	45cm
208XM-24-(color)	24"	60cm
208XM-48-(color)	48"	120cm
208XM-60-(color)	60"	150cm
208XMC-(color)	48" Coil Cord	



MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See Basic P/N AXM.
.250" (6.35mm) INSULATED SPADE LUG: Nickel-Plated Brass Lug. Plastic Handle.
 Solder Assembly. Red, Black. Red will be supplied with colors other than Black Unit. See P/N 9208.

MICRO-HOOK TO .140" (3.57mm) INSULATED SPADE LUG (Illustration NOT to Scale)

Standard Unit Part Number	22AWG	Lead Length
209XM-(color)	36"	90cm
209XM-12-(color)	12"	30cm
209XM-18-(color)	18"	45cm
209XM-24-(color)	24"	60cm
209XM-48-(color)	48"	120cm
209XM-60-(color)	60"	150cm
209XMC-(color)	48" Coil Cord	



MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See Basic P/N AXM.
.140" (3.57mm) INSULATED SPADE LUG: Tin-Plated Copper Lug. Plastic Handle. Solder Assembly. Red Spade Lug will be provided with any color unit. See P/N 9209.