

E-Z-MINI-HOOK XR HEAVY DUTY TEST LEADS

MINI-HOOK XR TO STACKING SHROUDED BANANA PLUG

Standard Unit Part Number	Lead Length	
635XR-(color)	36"	90cm
Additional Lengths		
635XR-12-(color)	12"	30cm
635XR-18-(color)	18"	45cm
635XR-24-(color)	24"	60cm
635XR-48-(color)	48"	120cm
635XR-60-(color)	60"	150cm
635XRC-(color)	60" Coil Cord	



STACKING SHROUDED BANANA PLUG: Male: Nickel-Plated Brass Body. Nickel-Plated Phosphor Bronze Springs. **Female:** Nickel-Plated BeCu Spring Socket. Plastic Handle. Solderless Assembly. Red, Black. Red will be supplied with colors other than Black Unit. Fits most Amprobe, Beckman, Simpson and Triplett Instruments. See P/N 9305.

MINI-HOOK XR TO STACKING SHROUDED RIGHT ANGLE STANDARD BANANA PLUG (Illustration NOT to Scale)


Standard Unit Part Number	Lead Length	
636XR-(color)	36"	90cm
Additional Lengths		
636XR-12-(color)	12"	30cm
636XR-18-(color)	18"	45cm
636XR-24-(color)	24"	60cm
636XR-48-(color)	48"	120cm
636XR-60-(color)	60"	150cm
636XRC-(color)	60" Coil Cord	



MINI-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See top of page.
STACKING SHROUDED BANANA PLUG: Nickel-Plated Brass Body and Socket. Nickel-Plated Phosphor Bronze Springs. Plastic Handle. Solderless Assembly. Red, Black. Red will be provided with colors other than Black. Fits most Fluke and B&K Precision Instruments. See P/N 9306.

MINI-HOOK XR WITH HEAVY DUTY LEAD TO .080" (2.03mm) PIN PLUG (Illustration NOT to Scale)


Standard Unit Part Number	Lead Length	
AX6XR-(color)	36"	90cm
Additional Lengths		
AX6XR-12-(color)	12"	30cm
AX6XR-18-(color)	18"	45cm
AX6XR-24-(color)	24"	60cm
AX6XR-48-(color)	48"	120cm
AX6XR-60-(color)	60"	150cm
AX6XRC-(color)	60" Coil Cord	



MINI-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See top of page.
.080" (2.03mm) PIN PLUG: Nickel-Plated Brass Body. Plastic Handle. Solderless Assembly. Red, Black. Red will be supplied with colors other than Black Unit. See P/N 9250.

MINI-HOOK XR WITH HEAVY DUTY LEAD TO STANDARD BANANA PLUG (Illustration NOT to Scale)


Standard Unit Part Number	Lead Length	
BX6XR-(color)	36"	90cm
Additional Lengths		
BX6XR-12-(color)	12"	30cm
BX6XR-18-(color)	18"	45cm
BX6XR-24-(color)	24"	60cm
BX6XR-48-(color)	48"	120cm
BX6XR-60-(color)	60"	150cm
BX6XRC-(color)	60" Coil Cord	



MINI-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See top of page.
STANDARD BANANA PLUG: Nickel-Plated Brass Body. Nickel-Silver Springs. Plastic Handle. Solderless Assembly. Red, Black. Red will be supplied with colors other than Black Unit. See P/N 9214.

MINI-HOOK XR WITH HEAVY DUTY LEAD TO STACKING BANANA PLUG (Illustration NOT to Scale)


Standard Unit Part Number	Lead Length	
601XR-(color)	36"	90cm
Additional Lengths		
601XR-12-(color)	12"	30cm
601XR-18-(color)	18"	45cm
601XR-24-(color)	24"	60cm
601XR-48-(color)	48"	120cm
601XR-60-(color)	60"	150cm
601XRC-(color)	60" Coil Cord	



MINI-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See top of page.
STACKING BANANA PLUG: Nickel-Plated Brass Body. Nickel-Silver Leaf Springs. Plastic Handle. Snap Together Solderless Assembly. See P/N 9260.

MINI-HOOK XR WITH HEAVY DUTY LEAD TO STACKING .080" (2.03mm) PIN PLUG (Illustration NOT to Scale)

Standard Unit Part Number	Lead Length	
602XR-(color)	36"	90cm
Additional Lengths		
602XR-12-(color)	12"	30cm
602XR-18-(color)	18"	45cm
602XR-24-(color)	24"	60cm
602XR-48-(color)	48"	120cm
602XR-60-(color)	60"	150cm
602XRC-(color)	60" Coil Cord	



MINI-HOOK, LEAD WIRE DESCRIPTIONS, TIP AND COLOR CHOICES: See top of page.
STACKING .080" (2.03mm) PIN PLUG: Nickel-Plated Brass Body. Plastic Handle. Solderless Assembly. See P/N 9259.