


E-Z-MICRO-HOOK TEST LEADS

MICRO-HOOK TO .080" (2.03mm) PIN PLUG

COLOR CHART	
Black	Green
Brown	Blue
Red	Violet
Orange	Gray
Yellow	White




.080" (2.03mm) PIN PLUG: Nickel-Plated Brass Body. Plastic Handle. Solderless Assembly See P/N 9201.

Standard Unit Part Number	22AWG	Lead Length
AXM-(color)	36"	90cm
Additional Lengths		
AXM-12-(color)	12"	30cm
AXM-18-(color)	18"	45cm
AXM-24-(color)	24"	60cm
AXM-48-(color)	48"	120cm
AXM-60-(color)	60"	150cm
AXMC-(color)	48" Coil Cord	

MICRO-HOOK:	Gold-Plated BeCu Contact per MIL G45204. Nylon Body with removable Plunger for easy service. Stainless Steel Spring. Hook fits component leads to .025" (.635mm) dia.
LEAD WIRE:	22AWG 65 x 40 Tinned Copper with extra flexible PVC Insulation. 28AWG 19 x 40 Tinned Copper with extra flexible PVC Insulation. 24AWG 19 x 36 Tinned Copper with Teflon Insulation. Temperature to 200°C.
COIL CORD:	22 AWG 26 x 36 PVC Insulated. Urethane Jacket. 7" Coil Length. 6" Pigtails. 48" Reach.
COLOR CHOICES	1. Single Color Unit: Add desired color to Part No. See Color Chart. Example: AXM-Red. 2. Color Assortment (1 ea of 10 Colors): Add -S after Part No. Example: AXM-S. 3. Multicolor Unit: See Kilo-Color Ordering Information on inside back cover.

MICRO-HOOK TO STANDARD BANANA PLUG (Illustration NOT to Scale)

Standard Unit Part Number	22AWG	Lead Length
BXM-(color)	36"	90cm
Additional Lengths		
BXM-12-(color)	12"	30cm
BXM-18-(color)	18"	45cm
BXM-24-(color)	24"	60cm
BXM-48-(color)	48"	120cm
BXM-60-(color)	60"	150cm
BXMC-(color)	48" Coil Cord	



MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See top of page.
STANDARD BANANA PLUG: Nickel-Plated Brass Body. Nickel-Silver Leaf Springs. Plastic Handle. Solderless Assembly. See P/N 9202.

MICRO-HOOK TO MINIATURE BANANA PLUG (Illustration NOT to scale)

Standard Unit Part Number	22AWG	Lead Length
CXM-(color)	36"	90cm
Additional Lengths		
CXM-12-(color)	12"	30cm
CXM-18-(color)	18"	45cm
CXM-24-(color)	24"	60cm
CXM-48-(color)	48"	120cm
CXM-60-(color)	60"	150cm
CXMC-(color)	48" Coil Cord	



MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See top of page.
STANDARD BANANA PLUG: Nickel-Plated Phosphor Bronze Body. Nickel-Plated BeCu Leaf Springs. Plastic Handle. Solder Assembly. See P/N 9213.

MICRO-HOOK TO STACKING BANANA PLUG (Illustration NOT to Scale)

Standard Unit Part Number	22AWG	Lead Length
201XM-(color)	36"	90cm
Additional Lengths		
201XM-12-(color)	12"	30cm
201XM-18-(color)	18"	45cm
201XM-24-(color)	24"	60cm
201XM-48-(color)	48"	120cm
201XM-60-(color)	60"	150cm
201XMC-(color)	48" Coil Cord	



MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See top of page.
STACKING BANANA PLUG: Nickel-Plated Brass Body. Nickel-Silver Leaf Springs. Plastic Handle. Solderless Assembly. See P/N 9203.

MICRO-HOOK TO STACKING .080" (2.03mm) PIN PLUG (Illustration NOT to Scale)

Standard Unit Part Number	22AWG	Lead Length
202XM-(color)	36"	90cm
Additional Lengths		
202XM-12-(color)	12"	30cm
202XM-18-(color)	18"	45cm
202XM-24-(color)	24"	60cm
202XM-48-(color)	48"	120cm
202XM-60-(color)	60"	150cm
202XMC-(color)	48" Coil Cord	



MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See top of page.
STACKING .080" (2.03mm) PIN PLUG: Nickel-Plated Brass Body. Plastic Handle. Solderless Assembly. See P/N 9204.

MICRO-HOOK TO METER BANANA PLUG (Illustration NOT to Scale)

Standard Unit Part Number	22AWG	Lead Length
205XM-(color)	36"	90cm
Additional Lengths		
205XM-12-(color)	12"	30cm
205XM-18-(color)	18"	45cm
205XM-24-(color)	24"	60cm
205XM-48-(color)	48"	120cm
205XM-60-(color)	60"	150cm
205XMC-(color)	48" Coil Cord	



MICRO-HOOK, LEAD WIRE DESCRIPTIONS AND COLOR CHOICES: See top of page.
METER BANANA PLUG: Nickel-Plated Brass Body. Phosphor Bronze Springs. Plastic Handle. Solder Assembly.
Red, Black. Red will be supplied with colors other than Black Unit. See P/N 9206.