

Heatsinks f.cool

Cases f.case

Connectors f.con

Sockets

PCB connectors

IDC-connectors

D-Sub connectors

D-Sub standard connectors

D-Sub connectors High Density

D-Sub filter connector

D-Sub connector for flat ribbon cable

D-Sub mixed layout connectors

D-Sub in SMD-mounting

D-Sub connector in pressfit technology

D-Sub hoods

D-Sub accessories

Brackets for PC

Optoelectronics

D-Sub connectors High Density

HD S ... L

HD S 15 L

Male headers

Data sheet

add to request



Features

Technical Drawing

Variants

Service

Accessories / related products

contact material	Cu-alloy
surface contact / contact sleeve	hard gold plated over nickel
quality class / cyces of operation	quality class 2 = 200 cycles of operation
volume resistance	≤10 mΩ before strain, ΔR 10 mΩ after strain according to DIN 41652. part 2 (MIL-C-24308)
air gap and creep distance	cont.-contact <0.6mm contact-earth <0.6mm
nominal current	3A (20°C)
nominal voltage	60 V AC
test voltage	1000 V
insulating body material	PBT, GF
temperature range	-55°C... +125°C
casing frame	steel, tin plated
class of inflammability	UL 94 V-0
insulation resistance	≥5 GΩ