



7x1.5mm SMD Tuning Fork Crystal


KFSX
(former FSXLF)
DATASHEET

Page 1 of 2


STANDARD SPECIFICATIONS

PARAMETERS	MAX (unless otherwise noted)
Frequency	32.768 kHz
Frequency Tolerance @ 25°C	(See options on page 2)
Frequency Stability (Temperature Coefficient)	-0.04 PPM / ($\Delta^\circ\text{C}$) ²
Temperature Range	
Turnover (T _O)	+20°C ~ +30°C
Operating (T _{OPR})	-40°C ~ +85°C
Storage (T _{STG})	-55°C ~ +125°C
Equivalent Series Resistance (R _s)	65 kΩ
Load Capacitance (C _L)	(See options on page 2)
Insulation Resistance @ 100VDC	500 MΩ Min
Drive Level	1.0 μW
Aging per year	±3 PPM
Maximum Soldering Temp / Time	260°C / 10 Seconds
Moisture Sensitivity Level (MSL)	1
Termination Finish	Matte Sn
Lead (Pb) Free	Exemption 7a
RoHS Compliant	Yes
REACH Compliance	Notification of Lead(Pb) >0.1%(w/w)

Temperature Coefficient



Mechanical / Dimensions (millimeters):



Note: Dimensional drawing is for reference to critical specifications defined by size measurements. Certain non-critical visual attributes, such as side castellations, etc. may vary.





7x1.5mm SMD Tuning Fork Crystal

KFSX
(former FSXLF)
DATASHEET


Page 2 of 2

• TAPE SPECIFICATIONS (millimeters)

A	B	C	D	E	F	Reel QTY
Ø1.55	4.0	4.0	7.5	16.0	1.6	T3 = 3,000

• REEL SPECIFICATIONS (millimeters)

G	H	I	J	K	L	M
2.0	Ø13	Ø21	Ø50	Ø180	17.0	2.2



Available Options & Part Identification for SMD Tuning Fork Crystal KFSX F KFSX E I H M 0.032768

F	KFSX	E	I	H	M	0.032768
<u>FOX</u>	<u>Model Number</u>	<u>Tolerance</u> E = ±20ppm	<u>Stability</u> I = -0.04 PPM / (Δ°C) ²	<u>Load Capacitance</u> V = 7pF H = 12.5pF	<u>Operating Temperature</u> M = -40 ~ +85 °C	<u>Frequency (MHz)</u>



Corporate
Headquarters
5570 Enterprise Parkway
Fort Myers, FL 33905
<http://www.FOXONLINE.com>

Sales
1-888-GET-2-FOX (1-888-438-2369) or
1-239-693-0099
<http://www.FOXONLINE.com/repdisty>

Tech Support
<http://www.FOXONLINE.com/email>

PRODUCT USE: Fox Electronics reserves the right to modify the products and/or specifications described herein at any time and at Fox Electronics' sole discretion. All information in this document, including descriptions of product features and performance, is subject to change without notice. Performance specifications and the operating parameters of the described products are determined in the independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied, including, but not limited to, the suitability of Fox Electronics' products for any particular purpose, an implied warranty of merchantability, or non-infringement of the intellectual property rights of others. This document is presented only as a guide and does not convey any license under intellectual property rights of Fox Electronics or any third parties. Fox Electronics' products are not intended for use in applications involving extreme environmental conditions or in life support systems or similar devices where the failure or malfunction of a Fox Electronics product can be reasonably expected to significantly affect the health or safety of users. Anyone using a Fox Electronics product in such a manner does so at their own risk, absent an express, written agreement by Fox Electronics. Fox Electronics and the Fox logo are registered trademarks of Fox Electronics. Product specification is subject to change without notice. Other trademarks and service marks used herein, including protected names, logos and designs, are the property of Fox Electronics or their respective third party owners. For datasheet type definitions and a glossary of common terms, visit <http://www.foxonline.com/tgcrystals.html>.



© Copyright 2020 Fox Electronics. All rights reserved

Title / Description: KFSX STANDARD SPECIFICATIONS

Drawing Number: KFSX-DOC-1

Size: A

Part Number:

Cage: 61429

Draftsperson: BEC

Approved: MAJ

Revision Date: 2/3/2020