




Press Center

About FSP

Products

Contact us









- 2x4 Series
- 3x5 Series
- 3x6 Series
- 4x7 Series
- Other Series



Click to ZOOM IN

FSP250-1FUA-12

All

40W - 400W > Other Series Dimensions : 214.5 x 120.4 x 40.5mm

Application: For information technology and industrial applications

Search

Email

Download PDF

Watt: 250W

c**51**® (**E**



- FSP400-1FUC-48
- FSP400-1FUC-36
- FSP400-1FUC-24
- FSP300-1FUA-24
- FSP250-1FUA-24

Downloaded from Arrow.com.



Introduction

Specification

Description

250W Open frame type power supply with 12V DC output for information technology and industrial applications

Application

For information technology and industrial applications

Features

- Compact size
- Fit 1U Chassis
- Full Load at 0~50 ℃
- Air Convection Cooling
- Protection: Over Voltage, Over Temperature, Short Circuit & Over Power
- High Reliability
- High Density
- MTBF 100,000 hours at 25°C

Adapter

- EMC class B
- ITE Approval



Storage











| Adapter | Industry | IPC PSU | Medical PSU | LED Lighting | PC PSU | Power Bank / | UPS | TV PSU |
|---|--------------|------------------------------------|--|---|---|--------------|-------------------------------|-------------------------------------|
| > Slim > Desktop > Wall Mount > USB PD Type C | > 40W - 400W | > 1U > 2U > FLEX > ATX/AT | > Medical PC PSU > Medical Open Frame | > Indoor Application > Outdoor Application | > ATX 12V > FLEX 12V > TFX 12V > SFX 12V | | > Line Interactive > Off Line | > 24"-38" > 39"-50" > 51"-70" |
| Series | | > SFX | Medical | Constant | | > Energy | On Line | |

Current

Output

DC-DC FLEX

DC-DC ATX

> Redundant Mini > Redundant 2U (CRPS) > Redundant 1U > PS2 Redundant > ATX/AT > Constant Voltage System

COPYRIGHT © 2013 FSP TECHNOLOGY INC. ALL RIGHTS RESERVED.

Tel: 886-3-375-9888 Fax: 886-3-375-6966 Email: <u>sales@fsp-group.com.tw</u>

CLICKY ANALYTICS