

## Major Appliance Cords

3 Conductor Grounded • Type SPT-3 • 15 and 20 AMPS • 60°C • 300 Volts

| CATALOG NUMBER | NO. OF COND. | AWG. SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING |      |       | NEMA CONFIG. | PKG. PER CTN. | WT./ UNIT LBS | WT./ CTN. LBS | UPC CODE     |
|----------------|--------------|-----------|---------------------|-----------------|--------------|------|-------|--------------|---------------|---------------|---------------|--------------|
|                |              |           |                     |                 | VOLTS        | AMPS | WATTS |              |               |               |               |              |
| 00436.63.17    | 3            | 14        | 6                   | Beige           | 125          | 15   | 1875  | 5-15P/5-15R  | 24            | 0.6           | 15            | 079407004362 |
| 00439.63.17    | 3            | 14        | 9                   | Beige           | 125          | 15   | 1875  | 5-15P/5-15R  | 24            | 0.9           | 21            | 079407004393 |
| 00442.63.17    | 3            | 14        | 12                  | Beige           | 125          | 15   | 1875  | 5-15P/5-15R  | 12            | 1.2           | 14            | 079407004423 |
| 00762.63.17    | 3            | 12        | 9                   | Beige           | 250          | 20   | 5000  | 6-20P/6-20R  | 24            | 1.4           | 34            | 079407007622 |
| 00772.63.17    | 3            | 12        | 9                   | Beige           | 125          | 20   | 2500  | 5-20P/5-20R  | 24            | 1.4           | 34            | 079407007721 |



### Product Construction:

#### Conductor:

- 12 and 14 AWG. stranded bare copper per ASTM B-174

#### Insulation:

- Premium-grade PVC; Beige

### Applications:

- Air conditioners
- Refrigerators
- Freezers
- Microwaves
- Dehumidifiers

### Features:

- Molded right-angle plug

### Industry Approvals:

- UL Listed

## Power Supply Replacement Cords

3 Conductor Grounded • Type SPT-1 and SPT-3 • 60°C • 300 Volts

| CATALOG NUMBER | CORD TYPE | NO. OF COND. | AWG. SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING |      |       | NEMA CONFIG. | PLUG CONFIG. | PKG. PER CTN. | WT./ UNIT LBS | WT./ CTN. LBS | UPC CODE     |
|----------------|-----------|--------------|-----------|---------------------|-----------------|--------------|------|-------|--------------|--------------|---------------|---------------|---------------|--------------|
|                |           |              |           |                     |                 | VOLTS        | AMPS | WATTS |              |              |               |               |               |              |
| 02050.70.10    | SPT-1     | 3            | 18        | 8                   | Gray            | 125          | 10   | 1250  | 5-15P        | Straight     | 50            | 0.4           | 21            | 079407020508 |
| 02522.73.01    | SPT-3     | 3            | 16        | 6                   | Black           | 125          | 13   | 1625  | 5-15P        | Straight     | 25            | 0.6           | 14            | 079407025220 |
| 04106.73.10    | SPT-3     | 3            | 16        | 6                   | Gray            | 125          | 13   | 1625  | 5-15P        | Right Angle  | 50            | 0.4           | 22            | 079407041060 |
| 04103.73.10    | SPT-3     | 3            | 16        | 3                   | Gray            | 125          | 13   | 1625  | 5-15P        | Right Angle  | 100           | 0.3           | 26            | 079407041039 |
| 04806.73.10    | SPT-3     | 3            | 16        | 6                   | Gray            | 125          | 13   | 1625  | 5-15P        | Straight     | 50            | 0.4           | 19            | 079407048069 |
| 04803.73.10    | SPT-3     | 3            | 16        | 3                   | Gray            | 125          | 13   | 1625  | 5-15P        | Straight     | 100           | 0.3           | 27            | 079407048038 |



### Product Construction:

#### Conductor:

- 18 AWG. and 16 AWG. stranded bare copper per ASTM B-174

#### Insulation:

- Premium-grade, color-coded PVC

#### Jacket:

- PVC; Black, Gray or Beige

### Applications:

- For replacement use

### Features:

- Conductor stripped 5/8"
- Free end slit 1 1/2"

### Industry Approvals:

- UL Listed