

尾注:

Globtek 公司不对未经批准而擅自修改部件而影响的~~安全~~和性能负责，终端用户必须参考 UL 、 CSA 或 EN 标准规定正确的安装。

Foot Note:

Globtek Inc. ~~will not be liable~~ for the safety and performance of these parts ~~if~~ unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instructions

禁用:

Globtek 产品未经授权不得使用于医疗设备中以及危险环境核试验或者飞机上，除非有 GLOBTEK 公司首席执行官的书面正式批准。

Limitation of Use:

Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

文件内容未经

Contents of th
are subject to c
without prior no

APPROVAL FLOW: 1.CUSTOMER
(INHOUSE/OUTSIDE)

2. ENG' G MANAGER
(CHECK/REVIEW)

3. MECH. ENGR
(DRAW/CHECK)

Technical drawing of a mechanical part, likely a connector or plug, showing dimensions: 2.0, 16.4, 9.7, and a diameter of 12.5. The drawing includes a cross-section view of the internal threads and a side view of the outer casing.

Tolerance table				PART NO 零
RANGE	GRADE 1	GRADE 2	GRADE 3	MODEL NO
X.X	± 0.05	± 0.1	$\pm 0.2\text{mm}$	Drawn and Checked By
X.XX	± 0.08	± 0.15	$\pm 0.1\text{mm}$	Double Checked By
x.xxx	± 0.12	± 0.25	$\pm 0.15\text{mm}$	Approved B
/	/	/	/	

4.ENG'G MANAGER
(REVIEW/APPROVED/FILE KEEPING-ENG'G and QAE ASSISTANT)

RELEASED

By N.Frost at 3:30 pm, Aug 21, 2018

ONS



	conditions/description	min	typ	max	units
voltage			50		Vdc
current				8	A
stand				30	mΩ
resistance		100			MΩ
stand	at 50/60Hz for 1 minute 1500 Vac	1500			Vac
humidity				98% (40°C)	
		10000			cycles

件号:	/	GlobTek(Suzhou), Co.,Ltd Tel: +86-512-6279-0301 Fax: +86-512-6279-0355 Web: www.globtek.cn			
型号:	/				
Brand:	Bruce	Tolerances: Grade 3	DRAWING FOR WIRE P/N: JACK-C-PANEL-8A (R)		
Model:					
Material:	Jet		A ₁	Rev. B	SHEET 1 OF 1

OPRN MANAGER

6.RELEASE TO MECH. ENGR

7.END CUSTOMER
(INHOUSE/OUTSIDE)



SPECIFICATIONS					
parameter	conditions/description	min	typ	max	units
rated input voltage			50		Vdc
rated input current				8	A
contact resistance				30	mΩ
insulation resistance		100			MΩ
voltage withstand	at 50/60Hz for 1 minute 1500 Vac	1500			Vac
Relative humidity				98%(40℃)	
life		10000			cycles

尾注: Globtek 公司不对未经批准而擅自修改部件影响的的安全和性能负责, 终端用户必须参考 UL、CSA 或EN标准规定正确的安装。 Foot Note: Globtek Inc. will not be liable for the safety and performance of these parts if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instructions	禁用: Globtek 产品未授权不得使用于医疗设备中以及危险环境核试验或者飞机上, 除非有 GLOBTEK 公司首席执行官的书面正式批准。 Limitation of Use: Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.	文件内容未经允许不得更改 Contents of this document are subject to change without prior notice	Tolerance table				PART NO 零件号:	/		GlobTek(Suzhou), Co.,Ltd Tel: +86-512-6279-0301 Fax: +86-512-6279-0355 Web: www.globtek.cn DRAWING FOR WIRE P/N: JACK-C-PANEL-8A (R)	A ₁	Rev. B	SHEET 1 OF 1
			RANGE	GRADE 1	GRADE 2	GRADE 3	MODEL NO 型号:	/					
			X.X	+/-0.05	+/-0.1	+/-0.2mm	Drawn and Checked By:	Bruce	Tolerances:				
			X.XX	+/-0.08	+/-0.15	+/-0.1mm	Double Checked By:	Grade 3					
			x.xxx	+/-0.12	+/-0.25	+/-0.15mm	Approved By:	Jet					
/	/	/	/										

APPROVAL FLOW: 1.CUSTOMER (INHOUSE/OUTSIDE) → 2.ENG'G MANAGER (CHECK/REVIEW) → 3.MECH. ENGR (DRAW/CHECK) → 4.ENG'G MANAGER (REVIEW/APPROVED/FILE KEEPING-ENG'G and QAE ASSISTANT) → 5.OPRN MANAGER → 6.RELEASE TO MECH. ENGR → 7.END CUSTOMER (INHOUSE/OUTSIDE)