



### Heat Shrinkable Tubing 3:1 in a Kit

#### ShrinkKit 321 Basic - black

The compact and handy kit belongs to the basic equipment for every assembler. Its ideal shrink ratio of 3:1 replaces many differently sized tubing.

#### Features and Benefits

- Compact and handy kit
- Black tubing
- Application range from 1 mm to 16 mm
- 220 precut pieces in five sizes



ShrinkKit 321 Basic.

 **Detailed Information about Heatguns please refer to page 529.**

<b>MATERIAL</b>	Polyolefin, cross-linked (PO-X)
<b>Shrink Ratio</b>	3:1
<b>Operating Temperature</b>	-55 °C to +135 °C
<b>Minimum Shrink Temperature</b>	+90 °C
<b>Longitudinal change after shrinkage</b>	+5 %/-10 % max.
<b>Dielectric Strength</b>	20 kV/mm according to ASTM D 2671
<b>Flammability</b>	Self extinguishing
<b>Insulation Class</b>	B (VDE 0530)
<b>Specifications</b>	SAE - AMS - DTL-23053/5 Class 1



Heat Shrinkable Tubing 3:1

**RoHS** 

COMP.	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Colour	Content (pcs.)	Article-No.
1	1.5	0.5	35.0	0.45	Black (BK)	50	380-03001
2	6.0	2.0	35.0	0.70	Black (BK)	30	
3	3.0	1.0	35.0	0.55	Black (BK)	25	
4	6.0	2.0	35.0	0.70	Black (BK)	15	
5	6.0	2.0	35.0	0.70	Black (BK)	15	
6	3.0	1.0	35.0	0.55	Black (BK)	25	
7	1.5	0.5	35.0	0.45	Black (BK)	50	
8	12.0	4.0	80.0	0.70	Black (BK)	5	
	18.0	6.0	80.0	0.80	Black (BK)	5	

All dimensions in mm. Subject to technical changes.



For product specific approvals and specifications please refer to the Appendix.