

Specification Sheet

Part Number: 596-00648



Pre-Printed Header Label, DANGER, 3.0" x 2.0", UV, PET, Red, 250/roll

Article Number	596-00648
Type	3X2DANGERUV
Color	Red (RD)
Features & Benefits	• Preprinted Solar Labels are made with UV-stable inks and materials for durability, weather resistance and long-term outdoor use. • Polyester is resistant to chemicals and solvents and will remain legible in dirty environments. • High abrasion and scuff resistance for high performance labeling. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	roll

Product Description	These labels come with preprinted color headers so only one color of ribbon is needed to complete the message panel. Labels can be used with TagPrint® Pro label software and HellermannTyton thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand.
Short Description	Pre-Printed Header Label, DANGER, 3.0" x 2.0", UV, PET, Red, 250/roll
Global Part Name	3X2DANGERUV-PET-RD
Technical Description	Pre-Printed Header Label, DANGER, 3" X 2", UV, Red
Width W (Imperial)	3.0
Width W (Metric)	76.2
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8
Width of Liner (Metric)	81.28
Width of Liner (imperial)	3.2
Material	Polyester (PET)
Material Shortcut	PET

Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	ANSI Standard Z535.4 IFC 2012 NEC2011 CSA 66956 UL 969 NEC2014
UL Recognized (US)	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	250
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.521
Weight (Imperial)	3.2

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)