

Specification Sheet

Part Number: 596-00840

NOMINAL OPERATING AC VOLTAGE	
NOMINAL OPERATING AC FREQUENCY	
MAXIMUM AC POWER	
MAXIMUM AC CURRENT	
MAX OVERCURRENT DEVICE RATING FOR AC MODULE PROTECTION	

Metal Solar Placard, Hand Writable, AC Module, 4.0" x 2.0", AA, Black, 5/pkg

Article Number 596-00840

Type AC2011M5

Color Black (BK)

Features & Benefits

- Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.
- Aggressive adhesive ensures strong bond, even on powder coated surfaces.
- Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.
- Optional Paint Shields provide additional protection for pre-printed and variable data placards.

Quantity Per pack

Product Description	Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, HellermannTyton offers two styles of variable placards: hand-writable and engravable. Both hand-writable placards feature a silver variable data area that can be marked using an industrial paint pen. Engravable placards have a black area that can be engraved using standard engraving equipment.
Short Description	Metal Solar Placard, Hand Writable, AC Module, 4.0" x 2.0", AA, Black, 5/pkg
Global Part Name	AC2011M5-AA-BK
Technical Description	4" X 2" Silver Aluminum text on black background that reads as: "NOMINAL AC VOLTAGE;NOMINAL OPERATING AC FREQUENCY;MAXIMUM AC POWER;MAXIMUM AC CURRENT;MAXIMUM OVERCURRENT DEVICE RATING FOR AC MODULE PROTECTION." 10 per pack. Nameplate is also printable using a paint pen to add the variable voltage information on demand.
Local Order Number 2	Cross Reference = Paint Shield: 596-00794
Length L (Imperial)	4.0
Length L (Metric)	101.6
Width W (Imperial)	4.00
Width W (Metric)	101.60
Height H (Imperial)	2.00
Height H (Metric)	50.80

Material	Anodized Aluminum (AA)
Material Shortcut	AA
Adhesive	Ultra High Bond Permanent Acrylic Adhesive
Halogen free	No
Adhesive Operating Temperature	from +50°F (from +10°C)
Operating Temperature (Metric)	-40°F to +203°F (-40°C to +95°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2014 NEC2017
Warranty (US)	Yes
Package Quantity(Imperial)	5
Package Quantity (Metric)	5
Customs Number	7616995195
Labels per Column	1
Labels per Row	1

Weight (Metric)	.104
------------------------	------

Weight (Imperial)	0.23
--------------------------	------