

596-00857

Article Number: 596-00857

Engravable Metal Solar Placard, PV AC DISCONNECT, 3.75" X 1.0", Aluminum, Black, 5/PK



Base Data

Local Order Number	596-00857
Type	ACDISCTM5ENG
Color	Black (BK)
Features and Benefits	- Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure. - Aggressive adhesive ensures strong bond, even on powder coated surfaces. - Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability. - Optional Paint Shields provide additional protection for pre-printed and variable data placards.
Product Description	Metal Solar Placards offer maximum durability for labeling photovoltaic equipment and components. A special printing process fuses UV stable inks to the placards for long-lasting results, tested to last up to 25 years - even in direct sunlight. Metal Solar Placards are designed to meet or exceed National Electrical Code (NEC) and the requirements of local Authorities Having Jurisdiction (AHJs), that may prefer a placard-style marking over thermal transfer printed labels.
Technical Description	3.75" X 1" Black text on aluminum background that reads as: "PHOTOVOLTAIC AC DISCONNECT." - 10 per pack. Nameplate can be used with standard engraving equipment to add variable data.
Short Description	Engravable Metal Solar Placard, PV AC DISCONNECT, 3.75" X 1.0", Aluminum, Black, 5/PK

Product Dimensions

Length L (Imperial)	3.75 "
Length L (Metric)	95.2 mm
Width W (Imperial)	3.75 "
Width W (Metric)	95.2 mm
Height H (Imperial)	1.0 "
Height H (Metric)	25.4 mm

Logistics and Packaging

Quantity Per	pack
Package Quantity	10
Package Quantity (Metric)	5

Material and Specifications

Material	Anodized Aluminum (AA)
Material Shortcut	AA
Adhesive	3M 300LSE Ultra High Bond Permanent Acrylic Adhesive
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	from +50°F (from +10°C)
Halogenfree	Yes
Operating Temperature	-40°F to +203°F (-40°C to +95°C)

ROHS Compliant Yes

UL Recognized (US) Yes