# **High Security Label Material**

## **Durattach Label Material**

HellermannTyton introduces a new concept in high security label marking. When indelible marking is needed in harsh chemical environments, the Durattach (DTH) label and ribbon combination, along with a standard thermal transfer printer, achieves extremely chemical and solvent resistant printing. The Durattach material can stand up to alcohol, toluene, acetone and other chemicals without the need for a clear plastic over-laminate to protect the printed text.

DTH is suited for printing process control labels and also the name plate labels, especially if high density barcoding or high quality printing is needed. The chemical and friction durability is excellent with superior print quality. In areas where the label must remain legible for security reasons, the Durattach DTH is an ideal solution.

The labels can be printed with the HellermannTyton's thermal transfer printing systems. The standard DTH ribbons will also provide a high quality mark on HellermannTyton Shrink-Tags.

# **Durattach Labels**


HellermannTyton Part No.	Description	Qty Per Roll
TAG13T4-DTH	.75" X .25" - 4 across	10000
TAG16T3-DTH	.9" X .25" - 3 across	10000
TAG15T3-DTH	1" X .5" - 3 across	10000
TAG27T2-DTH	1.5" X .75" - 2 across	10000
TAG99T1-DTH	2.0" X .25" - 1 across	2500
TAG73T1-DTH	2.0" X 1.0" - 1 across	3000
TAG33T1-DTH	3.0" X 2.0" - 1 across	1000

custom sizes available upon inquiry - minimums may apply.

Durattach labels + Durattach ribbon =
The most permanent mark in the industry

#### **Durattach Ribbon**

HellermannTyton Part No.	Length	Printer	Use With
TTDTHOUTSM	110 mm X 50 m	TT210SM or TT310SM	Shrink-Tags or Durattach Labels
TTDTHOUT	102mm X 300 m	TT1210	Shrink-Tags or Durattach Labels





# **Friction and Chemical Durability**

Description	Durattach DTH Label	General Polyester Label
Blank	0123	0123
Plastic Eraser 50 times	0123	0123
Plastic Eraser 100 times	0123	0123
Isopropyl Alcohol 20 times	0123	0123
Toluene 20 times	0123	
Acetone 20 times	0123	

#### **Test Method**

Friction durability - A label is rubbed back and forth 50 or 100 times with a plastic eraser.

Chemical durability - A label is rubbed back and forth 20 times with a load of 200 g applied to cotton soaked in each of several organic solvents.

Label Material	DTH High Density Polyolefin	
Topcoat	Specially formulated for indelible ink anchorage using DTH ribbon specifically	
Liner	50#	
Temp. Range	-40F to +140F (-40C to +60C)	
Adhesive Type	Acrylic	
Application	For flat or slightly curved surfaces only	

# **Printing Energy and Printing Speed**

Description	Durattach Label	General Polyester Label
Printing Energy	0.10mj/dot	0.13mj/dot
Printing Speed	57 pcs./min (30mm x 50mm)	46 pcs./min (30mm x 50mm)

HellermannTyton offers a complete identification product line including the Spirit® 2100 portable printing system, computer printable labels, TagPrint Pro™ labeling software package and an extensive line of printers, markers, signs and label books.



# HELLERMANNTYTON CORPORATE HEADQUARTERS NORTH AMERICA

7930 N. Faulkner Rd, PO Box 245017

Milwaukee, WI 53224

Phone: (414) 355-1130, (800) 537-1512 • Fax: (414) 355-7341 http://www.hellermann.tyton.com • email: corp@htamericas.com

### HELLERMANNTYTON CANADA

Beaver Creek Business Park Unit #1, 160 West Beaver Creek Richmond Hill, Ontario L4B 1E3 Canada Phone: (905) 882-8024, (800) 661-2461 Fax: (905) 882-1624, (800) 390-3904

### HELLERMANNTYTON MEXICO

Rio Conchos 1757 Colonia Industrial El Rosario Guadalajara, Jalisco, Mexico 44890 Phone: (3) 659-7020, 011-52-3-659-7020 (From U.S.)

Fax: (3) 659-6939