

Specification Sheet

Part Number: TAG15J-450



Ink Jet Label, 1.0" x .50", 117 Per Sheet, PET, White, 5000/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 593-15450                                                                                                                                                                                                                                                                                                                                                          |
| Type                | TAG15J                                                                                                                                                                                                                                                                                                                                                             |
| Color               | Black (BK)                                                                                                                                                                                                                                                                                                                                                         |
| Features & Benefits | <ul style="list-style-type: none"><li>• Ink jet printable polyester has a smooth surface, allowing for the highest resolution and print contrast.</li><li>• The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.</li><li>• When used with black pigment-based inks, the material can withstand chemicals and solvents.</li></ul> |
| Quantity Per        | pack                                                                                                                                                                                                                                                                                                                                                               |

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b>  | HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 450 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature marking. |
| <b>Short Description</b>    | Ink Jet Label, 1.0" x .50", 117 Per Sheet, PET, White, 5000/pkg                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Global Part Name</b>     | TAG15J-450-BK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Width W (Imperial)</b>   | 0.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Width W (Metric)</b>     | 12.7                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Thickness T (Metric)</b> | 64.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Height H (Imperial)</b>  | 1.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Height H (Metric)</b>    | 25.4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Material</b>             | Type 450, Polyethylene Terephthalate (450)                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Material Shortcut</b>    | 450                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Adhesive</b>             | Acrylic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Halogen free</b>         | No                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Adhesive Operating Temperature</b> | -40°F to +302°F (-40°C to +150°C) |
|---------------------------------------|-----------------------------------|

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Operating Temperature (Metric)</b> | -40°F to +302°F (-40°C to +150°C) |
|---------------------------------------|-----------------------------------|

|                                    |     |
|------------------------------------|-----|
| <b>Reach Complaint(Article 33)</b> | Yes |
|------------------------------------|-----|

|                       |     |
|-----------------------|-----|
| <b>ROHS Complaint</b> | Yes |
|-----------------------|-----|

|                                   |      |
|-----------------------------------|------|
| <b>Package Quantity(Imperial)</b> | 5000 |
|-----------------------------------|------|

|                                  |      |
|----------------------------------|------|
| <b>Package Quantity (Metric)</b> | 5000 |
|----------------------------------|------|

|                       |            |
|-----------------------|------------|
| <b>Customs Number</b> | 3919905060 |
|-----------------------|------------|

|                             |      |
|-----------------------------|------|
| <b>Content Unit(BMEcat)</b> | pcs. |
|-----------------------------|------|

|                          |   |
|--------------------------|---|
| <b>Labels per Column</b> | 9 |
|--------------------------|---|

|                       |    |
|-----------------------|----|
| <b>Labels per Row</b> | 13 |
|-----------------------|----|

|                        |       |
|------------------------|-------|
| <b>Weight (Metric)</b> | 0.521 |
|------------------------|-------|

|                          |      |
|--------------------------|------|
| <b>Weight (Imperial)</b> | 1.14 |
|--------------------------|------|